

Enhancing our communities



Strada Shelburne

Strada Aggregates Inc.

Document Control

File: Prepared by: Prepared for:

123016 Tatham Engineering Limited Strada Aggregates Inc.

115 Sandford Fleming Drive, Suite 200 30 Floral Parkway
Date: Collingwood, Ontario L9Y 5A6 Vaughan, Ontario L4K 4R1

March **T** 705-444-2565 28, 2024 tathameng.com

Authored by:	Reviewed by:
Amm	ALICIA KIMBERLEY PRACTISING MEMBER 2949 ONTARIO
Jordon Miller, B.Eng., EIT.	Alicia Kimberley, M.Sc., P.Geo.
Engineering Intern	Group Leader - Hydrogeology

Disclaimer	Copyright
The information contained in this document is solely for the use of the Client identified on the cover sheet for the purpose for which it has been prepared and Tatham Engineering Limited undertakes no duty to or accepts any responsibility to any third party who may rely upon this document.	This document may not be used for any purpose other than that provided in the contract between the Owner/Client and the Engineer nor may any section or element of this document be removed, reproduced, electronically stored or transmitted in any form without the express written consent of Tatham Engineering Limited.

Issue	Date	Description
1	March 28, 2024	Final Report

i

Document Contents

1	Introduction1
1.1	Site Description
2	Regulatory Requirements2
2.1	Water Taking2
2.2	Groundwater and Surface Water Monitoring Requirements2
3	2023 Compliance Monitoring Results6
3.1	Water Taking6
3.2	Groundwater Monitoring6
3.3	Surface Water
4	Conclusions 18
Tab	les
Tab	ole 1: Monitoring Details
Tab	le 2: 2023 Water Takings8
Tab	le 3: Manual Groundwater Elevations
Tab	le 4: Groundwater Sampling Locations and Parameters
Tab	le 5: Manual Surface Water Elevations
Fig	ures
Fig	ure 1: Site Location Plan
Fig	ure 2: Groundwater and Surface Water Monitoring Locations
Fig	ure 3: Series A 2023 Groundwater Levels
Fig	ure 4: Shallow Groundwater Contour Map - Spring 202322
Fig	ure 5: Shallow Groundwater Contour Map - Fall 202323
	ure 6: Series B 2023 Groundwater Levels
Fig	ure 7: Series C 2023 Groundwater Levels
Fig	ure 8: Deep Groundwater Contours - Spring 202326
Fig	ure 9: Deep Groundwater Contours - Fall 2023



Appendices

Appendix A: PTTW

Appendix B: Integrated Monitoring Plan

Appendix C: Borehole Logs Appendix D: Hydrographs

Appendix E: Water Quality Results

Appendix F: Domestic Water Monitoring Program Results



1 Introduction

Tatham Engineering Limited (Tatham) has been retained by Strada Aggregates Inc. (Strada) to complete the 2023 compliance monitoring and reporting for the Strada Shelburne pits comprising the Bonnefield/Prince Pits, Melancthon Pit #1, and Melancthon Pit #2, all located on Part Lot 11-13, Concession 3, in the Township of Melancthon.

1.1 SITE DESCRIPTION

The Strada Shelburne aggregate pits, hereafter referred to as the "site", are located northwest of Shelburne, north of Dufferin 17 between Line 4 and Line 3. The site is 152 ha in size and is surrounded by rural residential properties and agricultural lands with a separate aggregate operation located immediately west of the site. The site is licensed for aggregate extraction under the Ministry of the Natural Resources and Forestry (MNRF) Aggregate Resources Act (ARA) for extraction of aggregate above the water table. Class "A" Pit Above Water Licenses are licensed to extract sand and gravel within 1.5 m of the water table. The location of the Strada Shelburne aggregate pits are shown on Figure 1.



2 Regulatory Requirements

The Strada Shelburne pits are comprised of the Bonnefield/Prince properties, Melancthon Pit #1, and Melancthon Pit #2. Each property has been integrated into one all-encompassing operation, which includes a closed loop washing facility regulated under the Melancthon Pit #2 Ontario Water Resources Act, Section 34, Permit to Take Water (PTTW) No.: 3210-AKRL9C, included in Appendix A.

Melancthon Pit #1 is located on the West Half of Lot 13, Concession 3, and has been licensed under MNRF ARA License No. 12253 since 2004. Melancthon Pit #2 is located on the West Half of Part Lot 11 and 12, Concession 3, and has been licensed under MNRF ARA License No. 625155 since 2012.

The proposed Bonnefield and Prince properties, which are located on Part of West Half of Lots 12 and 13, Concession 3, have not yet been licensed, but the expectation is these extensions will be fully integrated with the existing aggregate operations.

To monitor the groundwater and surface water conditions throughout extraction, an integrated monitoring plan was developed by Whitewater Hydrogeology (2018) to effectively identify and characterize any cumulative influences on the groundwater and surface water regimes as a result of any extraction and/or washing operations on-site. A copy of the integrated monitoring plan is included in Appendix B.

This report has been prepared to comply with both the PTTW and integrated monitoring plan requirements.

2.1 WATER TAKING

Strada is required to monitor daily water takings in accordance with PTTW 3210-AKRL9C. This data is required to be reported every year to the Ministry's Water Taking Reporting System on or before March 31 of the following year. PTTW 3210-AKRL9C allows for the taking of 4,000 L/min for a maximum of 10 hours per day while ensuring water takings do not exceed 2,400,000 L/day for a maximum of 230 days between April 1 and November 16 of each year.

The permitted water taking is for the purposes of washing gravel in a closed loop system and does not include dust suppression.

2.2 GROUNDWATER AND SURFACE WATER MONITORING REQUIREMENTS

The required groundwater and surface water monitoring program is summarized in Table 1, and the monitoring locations are shown on Figure 2.



Table 1: Monitoring Details

MONITORING LOCATION ¹	PARAMETER	FREQUENCY					
INTEGRATED MONITORING PLAN REQUIREMENTS							
OW2A, OW2B, OW3B, OW4A, OW4B, OW5A, OW5B, OW6A, OW7C2, OW8A, OW9A, OW10A3, OW11A, OW11B, OW12A, OW13A, OW16C2, OW14C2, OW15B, OW16C2, OW18A, OW18C2, OW19A3, OW19C2, OW20C2, OW21C2, OW22C2, OW23C2	Water Level	Continuous data logger					
OW2A, OW2B, OW3B, OW4A, OW4B, OW5A, OW5B, OW6A, OW7A, OW7B, OW8A, OW9A, OW10A ³ , OW11A, OW11B, OW12A, OW13A, OW13C ² , OW14C, OW16C ² , OW18A, OW18C ² , OW19C ² , OW20C ² , OW21C ² , OW22C ² , OW23C ²	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity	Semi-Annual (spring and fall)					
OW5A, OW6A, OW7A, OW8A, OW9A, OW10A ³ , OW11A OW12A, OW14C ² , OW16C ² , OW18A, OW20C ² , OW21C	Oil and Grease, PHC (F1-F4), BTEX	Annual					
Wetland (SW1) and Vernal Pool (SW2)	Water Level	Continuous data logger					
	PTTW REQUIREMENTS						
Wash Pond ⁴ , OW2A, OW2B, OW2C, OW3A ³ , OW3B, OW4A, OW4B, OW4C ⁵ , OW5A, OW5B, OW5C, OW6A, OW7A, OW7C, OW8A, OW8B, OW9A, OW10A ³ , OW10B, OW11A, OW11C, OW12A, OW13A, North Pond, South Pond	Water Level	Continuous data logger					



MONITORING LOCATION ¹	PARAMETER	FREQUENCY
ADDIT	IONAL DUE DILIGENCE MONITO	DRING
North Pond, South Pond	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity, Phosphorus, Hardness	Semi-Annual (spring and fall)
North Pond, South Pond	Surface Water Level	Continuous data logger
DW1, DW2, DW3, DW4, DW5	Water Levels	Continuous data logger
DW1, DW2, DW3, DW4, DW5	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity, Phosphorus, Hardness	Semi-Annual (spring and fall)

Note:

- 1. OW2A, OW2B, OW2C, OW8B, OW11A, OW11B, OW15B, OW17A and OW17B have been destroyed.
- 2. OW7B, OW14B, OW16B, OW18B, OW19B, OW20B, OW21C, OW22C, and OW23C are now referred to as OW7C, OW14C, OW16C, OW18C, OW19C, OW20C, OW21C, OW22C, and OW23C, respectively.
- 3. Monitoring of OW3A, OW10A, OW19A, and OW20A has been discontinued as the monitors were consistently dry through the summer months.
- 4. The wash pond was removed and reconstruction has been on-going throughout 2023. As the location has not been permanently constructed monitoring has been discontinued for the time being.
- 5. Monitoring of OW4C was discontinued in 2016.
- 6. Monitoring of OW21A was discontinued because the monitor was plugged.
- 7. Monitoring of OW22A and OW23A has been discontinued as the deep and shallow groundwater levels were very similar. It is suspected that the well seal between the deep and shallow is not sufficient.

All three of the pits have an extensive history of groundwater monitoring, which have been a part of the development of the site's integrated monitoring plan. The PTTW requires water levels to be monitored at 23 groundwater monitoring wells and three surface water locations, and the integrated monitoring plan requires water levels to be monitored at 31 groundwater monitoring wells and two surface water locations. The integrated monitoring plan also requires groundwater quality to be monitored semi-annually at 27 locations and annually at 13 locations. In addition to both the PTTW and integrated monitoring plan, water levels and semi-annual water quality is monitored in five off-site domestic water wells and an additional two surface water locations.

Monitors labelled with an "A" as the suffix are screened at the base of the sand and gravel unit (water table aquifer). Monitors labelled with a "B" as the suffix are screened at the base of the Tavistock Till (just above the bedrock contact). Monitors labelled with a "C" as the suffix are



constructed within the bedrock aquifer. Borehole records are included in Appendix C for reference.

The groundwater monitoring program focuses on the on-going monitoring of background conditions (upgradient locations) in both the overburden and bedrock aquifers as well as the monitoring of potential influences from the aggregate operation on down-gradient locations.

It is noted three monitoring wells were retrofitted with nested monitoring wells (OW24A and C, OW25A and C and OW26A and C), and additional monitoring wells were constructed at OW27C, OW28A, OW28C, OW29A, OW29C and OW30C during the 2023 monitoring period. The additional monitoring locations were constructed as part of an on-going hydrogeological assessment in support of a below water table aggregate license. As the new monitoring locations were installed in the fall of 2023 the monitoring results measured to date have not been included in the 2023 annual compliance report. However, they will be included in the annual compliance reports moving forward.



3 2023 Compliance Monitoring Results

3.1 WATER TAKING

In 2023, water was taken on 115 days between April 26 and November 20. The maximum reported daily taking was 2,028,980.72 L. The reported water takings for 2023 remain within the permitted volumes in accordance with PTTW 3210-AKRL9C. The 2023 daily water takings are summarized in Table 2.

3.2 GROUNDWATER MONITORING

Groundwater levels from the on-site and off-site monitoring wells were collected over the 2023 monitoring period, and the highest and lowest groundwater levels observed are summarized in Table 3. The monitoring wells are equipped with continuously recording dataloggers to allow for a detailed analysis of the groundwater conditions at the site. This is to allow for the assessment of the seasonal trends as well as the response to local precipitation events. The data logger values have been calibrated against manual measurements and the 2023 hydrographs are provided in Appendix D.

3.2.1 Overburden Groundwater Elevations (Series A)

The groundwater elevations in the vicinity of the Strada properties are strongly influenced by the bedrock topography and the buried bedrock valley system reported in the southeast portion of the study area. This feature has created a primarily downward gradient from the shallow overburden aquifer to the bedrock aquifer. As a result, the overburden is dry in the north and northwestern portion of Melancthon Pit #1 as well as beneath the Prince property. Permanent unsaturated conditions in the overburden are reported at OW3A, OW10A, OW14A, OW19A, and OW20A, where the first water-bearing zone is found beneath the bedrock contact (bedrock aquifer).

Generally, the groundwater level trends within the overburden aquifer (Series A) are seasonal, with water levels peaking in the spring and decreasing over the warmer and drier summer months. A summary hydrograph with all Series A water levels is provided in Figure 3. The groundwater elevations on-site within the overburden aquifer ranged across the site from 499.89 to 487.42 metres above sea level (m asl), with the highest groundwater levels noted between April and May, due to the spring melt. In general, the groundwater levels observed on-site in 2023 are consistent with groundwater levels and trends historically observed on-site.



Groundwater contour maps have been prepared for the shallow aquifers, based on the April and December (spring and fall) site visits. The general groundwater flow direction appears to be towards the east central portion of the site and the southeastern corner of the site, respectively, as shown on Figures 4 and 5.

3.2.2 Bedrock/Till Contact Groundwater Elevations (Series B and C)

Like the overburden water levels, the water levels in the Till contact unit and weathered bedrock aquifer (bedrock contact) show muted seasonal trends where water level highs are reached during the spring, followed by a slight decrease during the summer, fall, and winter months. Water levels in the bedrock aquifer are less influenced by seasonal trends and remain relatively stable over the monitoring period.

The groundwater elevations on-site at the Till contact (Series B) ranged across the site from 498.44 to 487.20 m asl, and the groundwater elevations on-site within the bedrock aquifer (Series C) ranged across the site from 498.20 to 496.61 m asl, with the highest groundwater levels noted between April and May due to the spring melt. A summary hydrograph with all Series B and C water levels are provided on Figures 6 and 7 respectively.

Groundwater contour maps have been prepared for the bedrock aquifer based on the April and December (spring and fall) site visits. The general groundwater flow direction appears to be towards the east as shown on Figures 8 and 9.



Table 2: 2023 Water Takings

DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)
26-Apr-23		12-May-23	821,434.36	1-June-23	1,377,889.89	20-June-23	1,249,185.89
27-Apr-23	1,843,495.54	15-May-23	1,218,902.59	2-June-23	1,563,375.07	21-June-23	1,249,185.89
28-Apr-23	1,839,710.13	16-May-23	1,430,885.65	5-June-23	969,065.42	22-June-23	1,729,933.19
1-May-23	1,714,791.54	17-May-23	1,226,473.42	6-June-23	1,025,846.59	22-June-23	1,673,152.01
2-May-23	950,138.36	18-May-23	1,075,056.95	7-June-23	1,514,164.71	27-June-23	1,052,344.48
3-May-23		19-May-23	158,987.29	8-June-23	1,563,375.07	28-June-23	1,181,048.48
4-May-23	1,396,816.95	23-May-23	1,135,623.54	9-June-23	802,507.30	28-June-23	1,056,129.89
5-May-23	1,574,731.30	24-May-23	1,813,212.24	12-June-23	401,253.65	29-June-23	1,676,937.42
6-May-23	1,510,379.30	25-May-23	1,022,061.18	13-June-23		30-June-23	1,631,512.48
8-May-23	1,510,379.30	26-May-23		14-June-23	620,807.53	4-July-23	1,003,134.12
9-May-23	1,873,778.83	29-May-23	586,738.83	15-June-23	1,782,928.95	5-July-23	651,090.83
10-May-23	1,866,208.01	30-May-23	1,760,216.48	16-June-23	1,854,851.77	6-July-23	726,799.06
11-May-23	1,162,121.42	31-May-23	1,756,431.07	19-June-23	1,067,486.12	7-July-23	1,661,795.77



DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)
10-July-23	972,850.83	27-July-23	1,593,658.36	17-Aug-23	1,866,208.01	7-Sep-23	1,885,135.07
11-July-23		28-July-23	1,642,868.71	18-Aug-23	1,438,456.48	8-Sep-23	1,673,152.01
12-July-23	1,854,851.77	31-July-23	1,131,838.12	21-Aug-23	1,090,198.59	11-Sep-23	
13-July-23	1,907,847.54	1-Aug-23	647,305.42	22-Aug-23	1,881,349.66	15-Sep-23	1,131,838.12
14-July-23	1,824,568.48	2-Aug-23	1,983,555.77	23-Aug-23	1,022,061.18	18-Sep-23	1,146,979.77
17-July-23	1,181,048.48	3-Aug-23	980,421.65	24-Aug-23	1,919,203.77	18-Sep-23	495,888.94
18-July-23	1,983,555.77	4-Aug-23	1,680,722.83	25-Aug-23	934,996.71	19-Sep-23	1,711,006.13
19-July-23	1,900,276.72	8-Aug-23	934,996.71	28-Aug-23	1,143,194.36	20-Sep-23	1,673,152.01
20-July-23	1,885,135.07	9-Aug-23	1,911,632.95	29-Aug-23	1,487,666.83	21-Sep-23	1,570,945.89
21-July-23	1,491,452.24	10-Aug-23	2,017,624.48	30-Aug-23	1,328,679.54	22-Sep-23	1,658,010.36
24-July-23		11-Aug-23	1,854,851.77	31-Aug-23	1,911,632.95	25-Sep-23	1,294,610.83
24-July-23	681,374.12	14-Aug-23	1,317,323.30	1-Sep-23	1,438,456.48	26-Sep-23	1,688,293.66
25-July-23	1,922,989.19	15-Aug-23	2,028,980.72	5-Sep-23	882,000.95	27-Sep-23	1,767,787.30



DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)	DATE	TOTAL DAILY TAKING (L)
26-July-23	1,953,272.48	16-Aug-23		6-Sep-23	1,858,637.19	28-Sep-23	1,230,258.83
29-Sep-23	1,328,679.54	16-Oct-23	1,146,979.77	30-Oct-23		13-Nov-23	870,644.71
2-Oct-23	1,097,769.42	17-Oct-23	1,695,864.48	31-Oct-23	1,033,417.42	14-Nov-23	1,782,928.95
3-Oct-23	1,563,375.07	18-Oct-23	1,654,224.95	1-Nov-23	1,695,864.48	15-Nov-23	1,692,079.07
4-Oct-23	1,646,654.13	19-Oct-23	1,563,375.07	3-Nov-23	1,582,302.13	16-Nov-23	1,722,362.36
5-Oct-23	1,692,079.07	20-Oct-23		3-Nov-23	1,457,383.54	17-Nov-23	1,536,877.18
6-Oct-23	1,680,722.83	23-Oct-23	1,101,554.83	6-Nov-23	1,131,838.12	20-Nov-23	1,037,202.83
10-Oct-23	1,063,700.71	24-Oct-23	1,536,877.18	7-Nov-23	1,105,340.24		
11-Oct-23	1,616,370.83	25-Oct-23	934,996.71	8-Nov-23	1,184,833.89		
12-Oct-23	1,782,928.95	26-Oct-23	1,733,718.60	9-Nov-23	1,260,542.12		
13-Oct-23	1,305,967.07	27-Oct-23	1,869,993.42	10-Nov-23	476,961.88		



Table 3: Manual Groundwater Elevations

WELL IDENTIFICATION	LOCATION (UTM NAD83)	GROUND ELEVATION	WELL DEPTH	GROUNDWATER LEVEL ELEVATION (m asl)		
		(m asl)	(m bgs)	HIGH	LOW	
OW3B	17T 561273E, 4886844N	504.47	12.80	493.68	491.09	
OW4A	17T 561355E, 4886425N	505.52	7.92	498.09	497.68	
OW4-B	17T 561355E, 4886425N	505.52	13.72	498.44	497.51	
OW5-A	17T 561738E, 4886523N	493.51	5.70	490.98	488.69	
OW5-B	17T 561738E, 4886523N	493.51	10.05	492.64	488.34	
OW5-C	17T 561738E, 4886520N	493.61	13.10	492.62	488.84	
OW6-A	17T 561663E, 4886939N	494.13	7.80	493.30	490.14	
OW7-A	17T 561771E, 4886674N	497.18	10.05	491.68	492.22	
OW7-C	17T 561773E, 4886668N	496.98	30.60	489.77	488.25	
OW8-A	17T 561282E, 4887057N	504.93	12.00	497.30	497.16	
OW9-A	17T 561798E, 4887451N	496.51	6.40	493.43	491.02	
OW10-B	17T 561632E, 4887297N	495.45	19.20	490.35	487.20	
OW12-A	17T 561882E, 4887192N	495.70	7.62	493.36	492.09	
OW13-A	17T 561140E, 4887598N	506.78	14.34	499.89	492.12 (dry)	
OW13-C	17T 561140E, 4887598N	506.78	18.94	496.77	491.66 (dry)	



WELL IDENTIFICATION	ELEVATION		WELL DEPTH	GROUNDWATER LEVEL ELEVATION (m asl)	
			(m bgs)	HIGH	LOW
OW14-C	17T 561763E, 4887841N	496.82	20.00	483.44	479.82
OW16-C	17T 561726E, 4887993N	497.11	27.30	482.14	477.47
OW18-A	17T 561653E, 4887685N	501.21	19.80	488.49	487.42
OW18-C	17T 561653E, 4887685N	501.21	23.70	486.77	484.49
OW19-C	17T 561036E, 4888192N	510.32	35.50	484.28	481.74
OW20-C	17T 561544E, 4888333N	509.30	26.40	485.83	485.29
OW21-C	17T 561593E, 4888680N	511.41	25.30	487.70	487.17
OW22-C	17T 561384E, 4888890N	513.66	27.50	498.20	497.19
OW23-C	17T 560938E, 4888787N	510.31	29.50	497.79	496.61
DW1	17T 562951E, 4886286N	479.67	-	497.18	496.61
DW2	17T 562704E, 4888248N	482.36	-	473.14	472.14
DW3	17T 562373E, 4887677N	493.92	-	477.95	468.32
DW4	17T 562197E, 4890008N	486.02	-	483.33	479.78
DW5	17T 559538E, 4889095N	517.26	-	512.27	508.05



3.2.3 **Groundwater Quality**

To monitor groundwater conditions, representative groundwater samples were collected for the spring event on March 22 and March 28, 2023, and the fall event on October 20 and October 25, 2023. A summary of the sampled locations and parameters tested are summarized in Table 4.

Table 4: Groundwater Sampling Locations and Parameters

SAMPLING EVENT	SAMPLING TYPE	LOCATIONS SAMPLED	PARAMETERS TESTED
		On-Site Monitoring Wells	
March 22 and 28, 2023	Semi-Annual	OW4A, OW4B, OW5A, OW5B, OW6A, OW7A, OW7B, OW8A, OW9A, OW10A ¹ , OW12A, OW13A, OW13C, OW14C, OW16C, OW18A, OW18C, OW19C, OW20C, OW21C, OW22C, OW23C	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity
	Annual	OW5A, OW6A, OW7A, OW8A, OW9A, OW10A ¹ , OW12A, OW14C, OW16C, OW18C, OW20C, OW21C	Oil and Grease, PHC (F1-F4), BTEX
October 18, 2023	Semi-Annual	OW4A, OW4B, OW5A, OW5B, OW6A, OW7A, OW7C, OW8A, OW9A, OW10A, OW12A, OW13C, OW14C, OW18A, OW18C, OW20C, OW21C, OW22C, OW23C	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity,
		Domestic Water Wells	
October 4, 2022 and February 27, 2023	Semi-Annual	DW1, DW2, DW3, DW4, DW5	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity, Phosphorous, Hardness
October 17, 2023	Domestic	DW1, DW2, DW3, DW4, DW5	Sulphate, Nitrates/Nitrites, ODWS Metals, Chloride, Alkalinity, Bicarbonate, pH, Conductivity, Phosphorous, Hardness

Note:

¹⁾ OW10A did not have sufficient water to sample during the spring groundwater sampling round.



Each sample was collected using dedicated waterra tubing and was placed directly into precleaned laboratory supplied vials and bottles with analytical test group specific preservatives. Dedicated nitrile gloves were used during sampling and non-dedicated equipment was sanitized between monitoring wells.

Samples were analyzed by Caduceon Environmental Laboratories (Caduceon), a CALA accredited lab, in Barrie. Groundwater chemistry results are included in the laboratory Certificates of Analysis included in Appendix E for reference.

The results were compared to the applicable Ontario Drinking Water Standards (ODWS) for due diligence purposes. Groundwater on-site generally met the applicable ODWS with the exception of:

- Hardness in the majority of the on-site monitors, which is typical for till and bedrock aquifers in southern Ontario;
- Nitrate in OW4A, 4B, 8A and 9A, which are assumed to be a result of the neighbouring agricultural activities;
- Aluminum in OW5A, 21C, and 23C, which is an ODWS Operational Guideline rather than an environmental or health related limit:
- Sodium in OW4B, 5A and 5B, which is assumed to be a result of the de-icing substances applied to County Road 17 located immediately to the south of these monitors;
- Manganese in OW7C, which is an ODWS Aesthetic Objective rather than an environmental or health related limit; and
- Iron in OW21C, which is typical for a bedrock aguifer in southern Ontario.

The results from 2023 are comparable to the historical ranges in concentrations reported at the monitoring wells. Further, no PHCs were noted in any of the tested wells.

The domestic water wells were also sampled and the individual homeowner letters for both the spring and fall sampling events are provided in Appendix F. 2023 was the first year which included water quality sampling of off-site private water wells. The groundwater was generally in compliance with the applicable Ontario Drinking Water Standards (ODWS) with the exception of hardness, manganese and iron which are still considered typical for bedrock water wells in southern Ontario. Further elevated concentrations of lead were noted in DW1 and DW3, however, after re-sampling from an indoor tap the lead concentrations were below the ODWS. As such, the elevated lead concentrations are considered to be erroneous. On both occasions the homeowner was notified regarding the elevated lead concentrations.



3.3 **SURFACE WATER**

Historically surface water monitoring has been completed during unfrozen conditions across the site at the North Pond, South Pond, Wash Pond, Vernal Pool (SW2), and Wetland (SW1). Historically, water levels within the Wash Pond have not been able to be collected due to issues with access, and data loggers were continually damaged as a result of the on-going aggregate activities. In 2024, a new approach to monitoring water levels in the Wash Pond will be initiated.

Surface water levels at the four on-site monitoring locations were collected over the 2023 monitoring period, and the highest and lowest surface levels observed are summarized in Table 5. The surface water locations are equipped with continuously recording dataloggers to allow for a detailed analysis of the water conditions at the site. This is to allow for the assessment of the seasonal trends as well as the response to local precipitation events. The data logger values have been calibrated against manual measurements and the 2023 hydrographs are provided in Appendix D.



Table 5: Manual Surface Water Elevations

LOCATION	COORDINATES		WATER LEVEL DEPTH (m)	
		High	Low	
North Pond	17T 561630E, 4887268N	494.02	491.31 (Dry)	
South Pond	17T 561778E, 4887155N	491.76	491.28 (Dry)	
SW1 (Wetland)	17T 561767E, 4887622N	100.311	99.68 ¹	
SW2 (Vernal Pool)	17T 561734E, 4887538N	100.291	99.671	

Note:

3.3.1 North and South Ponds

The North Pond and South Pond were measured using a datalogger tied to a string and a tree. The logger was thrown into the middle of the pond, and not removed throughout the year to try and keep results consistent.

Generally, the surface water level trends within the North and South Ponds are seasonal, with water levels peaking in the spring and decreasing over the warmer and drier summer months. The surface water elevations in the North and South Ponds ranged from 494.02 to 491.28 m asl, with the highest surface water levels noted between April and May, due to the spring melt. The North Pond dried out in the late fall, and the South Pond dried out between May and October. Dataloggers were removed in the late fall to limit damage to the devices. Hydrographs for the North and South Ponds are provided in Appendix D. Based on historical groundwater level monitoring it is assumed both the North and South Ponds are perched above the overburden aquifer.

In general, the surface water levels observed on-site in 2023 are consistent with surface water levels and trends historically observed on-site.



^{1.} For SW1 and SW2 a relative elevation of 100 m asl was assumed to assess seasonal changes in the surface water levels.

3.3.2 SW1 and SW2

SW1 and SW2 are located within the forested area approximately 100 m from the proposed extraction boundary of the Bonnefield Pit. Both features are perched above the water table and therefore isolated from the groundwater regime.

SW1 and SW2 were constructed by driving a steel, screened well point approximately 1 m into the ground. A steel pipe was attached to the top of this drive point so it could be easily located. SW1 was replaced and relocated in 2023 due to vandalism. These monitors are subject to freeze/thaw cycles and ice movement since they stay in all year round. As such, the data from year to year may vary slightly.

Generally, the surface water level trends at SW1 and SW2 are seasonal, with water levels peaking in the spring and decreasing over the warmer and drier summer months. The surface water elevations at SW1 and SW2 ranged from an elevation of 100.31 to 99.68 m, with the highest surface water levels noted between April and May, due to the spring melt. SW1 and SW2 both dried out in 2023 in late fall. Dataloggers were removed in the late fall to limit damage to the devices. Hydrographs for the North and South Ponds are provided in Appendix D.

In general, the surface water levels observed on-site in 2023 are consistent with surface water levels and trends historically observed on-site.

3.3.3 **Surface Water Chemistry**

To monitor surface conditions, representative surface water samples were collected from the North and South Pond on May 24 and October 19, 2023, and submitted for chemical analysis of sulphate, nitrates/nitrites, ODWS metals, chloride, alkalinity, bicarbonate, pH, conductivity, phosphorous, and hardness.

The samples were collected and placed directly into pre-cleaned laboratory supplied vials and bottles with analytical test group specific preservatives. Dedicated nitrile gloves were used during sampling.

Samples were analyzed by Caduceon, a CALA accredited lab, in Barrie. Surface water chemistry results are included in the laboratory Certificates of Analysis provided in Appendix E.

The results were compared to the applicable Provincial Water Quality Objectives (PWQO) for due diligence purposes. Surface water on-site generally met the applicable PWQO with the exception of iron during the fall sampling round at the North Pond. Further, elevated concentrations of phosphorous were noted during the fall sampling round when compared to interim PWQO. The 2023 water quality results are similar to previous years.




Conclusions

The compliance monitoring in support of the Bonnefield/Prince properties, Melancthon Pit #1 and Melancthon Pit #2 in 2023 was completed in accordance with the integrated monitoring plan developed for the aggregate operation and PTTW No. 3210-AKRL9C. The monitoring included surface and groundwater level monitoring and quality sampling at 24 groundwater monitoring wells. 5 surface water locations and 5 domestic wells in 2023.

In addition, the daily water takings were monitored and recorded for submission to the MECP via the Ministry's Water Taking Reporting System. The results of the 2023 monitoring program are summarized as follows:

- The maximum recorded water taking was 2,028,981 L in 2023 and the water takings remained in compliance with the conditions of PTTW No. 3210-AKRL9C;
- The overburden groundwater elevations are seasonal, peaking in the spring and decreasing over the summer months, and the 2023 monitoring results are consistent with historic trends;
- The bedrock/till groundwater elevations show muted seasonal trends, with highs in the spring followed by slight declines through the summer, and the 2023 monitoring results are consistent with historic trends:
- The groundwater quality on-site generally met the applicable OPWS with a few noted exceptions, however, the 2023 results are comparable to the historic trends and no PHCs were noted in any of the tested wells;
- The water levels in the north and south ponds varied seasonally over the year, with highs in the spring and drying out over the summer or fall, and the 2023 monitoring results are consistent with the historic trends;
- The water levels at SW1 and SW2 varied seasonally in 2023, with highs in the spring and drying out in the fall, and the 2023 monitoring results are consistent with the historic trends;
- The surface water quality on-site generally met the application PWQO, with the exception of iron in the north pond and phosphorus during the fall sampling round; but the results are consistent with trends; and
- The wash pond water levels were unable to be obtained in 2023 due to access issues and a damaged data logger and a new monitoring approach will be employed in 2024 to resolve this issue.







1. COORDINATE SYSTEM: NAD 1983 UTM ZONE 17N
2.CONTAINS INFORMATION LICENSED UNDER THE OPEN GOVERNMENT LICENSE - ONTARIO.

LEGEND

SITE

♦ DOMESTIC WELLS

DESTROYED WELLS

▼ SURFACE WATER LOCATIONS





Figure 3: Series A 2023 Groundwater Levels







ONTARIO.

1. COORDINATE SYSTEM: NAD 1983 UTM ZONE 17N 2.CONTAINS INFORMATION LICENSED UNDER THE OPEN GOVERNMENT LICENSE -

LEGEND


SITE

APRIL MONITORING WELLS -SHALLOW

--- GROUNDWATER CONTOUR

→ GROUNDWATER FLOW DIRECTION

GROUNDWATER ELEVATION (TAKEN APRIL 26,27, 2023)



SCALE: 1:12,000

DRAWN: AO

DATE: MAR. 2024

JOB NO. 123016



1. COORDINATE SYSTEM: NAD 1983 UTM ZONE 17N

2.CONTAINS INFORMATION LICENSED UNDER THE OPEN GOVERNMENT LICENSE - ONTARIO.

LEGEND

SITE

DECEMBER MONITORING WELLS - SHALLOW

--- GROUNDWATER CONTOUR

→ GROUNDWATER FLOW DIRECTION

Q GROUNDWATER ELEVATION (TAKEN DECEMBER 11, 2023)




Figure 6: Series B 2023 Groundwater Levels







Figure 7: Series C 2023 Groundwater Levels







1. COORDINATE SYSTEM: NAD 1983 UTM ZONE 17N

2.CONTAINS INFORMATION LICENSED UNDER THE OPEN GOVERNMENT LICENSE -ONTARIO.

LEGEND


SITE

APRIL MONITORING WELLS -DEEP

--- GROUNDWATER CONTOUR

→ GROUNDWATER FLOW DIRECTION

GROUNDWATER ELEVATION (TAKEN APRIL 26,27, 2023)





1. COORDINATE SYSTEM: NAD 1983 UTM ZONE 17N
2.CONTAINS INFORMATION LICENSED UNDER THE OPEN GOVERNMENT LICENSE - ONTARIO.

LEGEND


SITE

DECEMBER MONITORING WELLS - DEEP


--- GROUNDWATER CONTOUR

→ GROUNDWATER FLOW DIRECTION

GROUNDWATER ELEVATION (TAKEN DECEMBER 11, 2023)



Appendix A: PTTW





PERMIT TO TAKE WATER

Ground Water NUMBER 3210-AKRL9C

Pursuant to Section 34.1 of the <u>Ontario Water Resources Act</u>, R.S.O. 1990 this Permit To Take Water is hereby issued to:

Strada Aggregates Inc. 30 Floral Parkway Vaughan, Ontario L4K 4R1

For the water Shelburne South Pit - Wash Pond

taking from:

Located at: Lot 11 and 12, Concession 3, Geographic Township of Melancthon

Melancthon, County of Dufferin

For the purposes of this Permit, and the terms and conditions specified below, the following definitions apply:

DEFINITIONS

- (a) "Director" means any person appointed in writing as a Director pursuant to section 5 of the OWRA for the purposes of section 34.1, OWRA.
- (b) "Provincial Officer" means any person designated in writing by the Minister as a Provincial Officer pursuant to section 5 of the OWRA.
- (c) "Ministry" means Ontario Ministry of the Environment and Climate Change.
- (d) "District Office" means the Guelph District Office.
- (e) "Permit" means this Permit to Take Water No. 3210-AKRL9C including its Schedules, if any, issued in accordance with Section 34.1 of the OWRA.
- (f) "Permit Holder" means Strada Aggregates Inc..
- (g) "OWRA" means the *Ontario Water Resources Act*, R.S.O. 1990, c. O. 40, as amended.

You are hereby notified that this Permit is issued subject to the terms and conditions outlined below:

TERMS AND CONDITIONS

1. Compliance with Permit

- 1.1 Except where modified by this Permit, the water taking shall be in accordance with the application for this Permit To Take Water, dated September 18, 2016 and signed by Grant C. Horan, and all Schedules included in this Permit.
- 1.2 The Permit Holder shall ensure that any person authorized by the Permit Holder to take water under this Permit is provided with a copy of this Permit and shall take all reasonable measures to ensure that any such person complies with the conditions of this Permit.
- 1.3 Any person authorized by the Permit Holder to take water under this Permit shall comply with the conditions of this Permit.
- 1.4 This Permit is not transferable to another person.
- 1.5 This Permit provides the Permit Holder with permission to take water in accordance with the conditions of this Permit, up to the date of the expiry of this Permit. This Permit does not constitute a legal right, vested or otherwise, to a water allocation, and the issuance of this Permit does not guarantee that, upon its expiry, it will be renewed.
- 1.6 The Permit Holder shall keep this Permit available at all times at or near the site of the taking, and shall produce this Permit immediately for inspection by a Provincial Officer upon his or her request.
- 1.7 The Permit Holder shall report any changes of address to the Director within thirty days of any such change. The Permit Holder shall report any change of ownership of the property for which this Permit is issued within thirty days of any such change. A change in ownership in the property shall cause this Permit to be cancelled.

2. General Conditions and Interpretation

2.1 Inspections

The Permit Holder must forthwith, upon presentation of credentials, permit a Provincial Officer to carry out any and all inspections authorized by the OWRA, the *Environmental Protection Act*, R.S.O. 1990, the *Pesticides Act*, R.S.O. 1990, or the *Safe Drinking Water Act*, S. O. 2002.

2.2 Other Approvals

The issuance of, and compliance with this Permit, does not:

- (a) relieve the Permit Holder or any other person from any obligation to comply with any other applicable legal requirements, including the provisions of the *Ontario Water Resources Act*, and the *Environmental Protection Act*, and any regulations made thereunder; or
- (b) limit in any way any authority of the Ministry, a Director, or a Provincial Officer, including the authority to require certain steps be taken or to require the Permit Holder to furnish any further information related to this Permit.

2.3 Information

The receipt of any information by the Ministry, the failure of the Ministry to take any action or require any person to take any action in relation to the information, or the failure of a Provincial Officer to prosecute any person in relation to the information, shall not be construed as:

- (a) an approval, waiver or justification by the Ministry of any act or omission of any person that contravenes this Permit or other legal requirement; or
- (b) acceptance by the Ministry of the information's completeness or accuracy.

2.4 Rights of Action

The issuance of, and compliance with this Permit shall not be construed as precluding or limiting any legal claims or rights of action that any person, including the Crown in right of Ontario or any agency thereof, has or may have against the Permit Holder, its officers, employees, agents, and contractors.

2.5 Severability

The requirements of this Permit are severable. If any requirements of this Permit, or the application of any requirements of this Permit to any circumstance, is held invalid or unenforceable, the application of such requirements to other circumstances and the remainder of this Permit shall not be affected thereby.

2.6 Conflicts

Where there is a conflict between a provision of any submitted document referred to in this Permit, including its Schedules, and the conditions of this Permit, the conditions in this Permit shall take precedence.

3. Water Takings Authorized by This Permit

Expiry 3.1

This Permit expires on **March 31, 2027**. No water shall be taken under authority of this Permit after the expiry date.

3.2 Amounts of Taking Permitted

The Permit Holder shall only take water from the source, during the periods and at the rates and amounts of taking specified in Table A. Water takings are authorized only for the purposes specified in Table A.

Table A

	Source Name / Description:	Source: Type:	Taking Specific Purpose:	Taking Major Category:	Max. Taken per Minute (litres):	Max. Num. of Hrs Taken per Day:		Max. Num. of Days Taken per Year:	Zone/ Easting/ Northing:
1	Wash Pond	Pond Dugout	Aggregate Washing	Industrial	4,000	10	2,400,000	230	17 561589 4887164
						Total Taking:	2,400,000		

- 3.3 Water taking under the authorization of this Permit shall only occur to a maximum of 230 days between April 1 and November 16 of each year from date of issue to March 31, 2027.
- 3.4 This Permit is issued for the sole purpose of washing gravel in a closed loop system where the majority of the water is recirculated and does not include dust suppression.
- 3.5 Prior to taking of water under this Permit, the Permit Holder shall ensure that any and all applicable permits or authorizations are obtained from Federal and Provincial Agencies having legislative mandates in water resources management.

4. Monitoring

- 4.1 Under section 9 of O. Reg. 387/04, and as authorized by subsection 34(6) of the *Ontario Water Resources Act*, the Permit Holder shall, on each day water is taken under the authorization of this Permit, record the date, the volume of water taken on that date and the rate at which it was taken. The daily volume of water taken shall be measured by a flow meter or calculated in accordance with the method described in the application for this Permit, or as otherwise accepted by the Director. The Permit Holder shall keep all records required by this condition current and available at or near the site of the taking and shall produce the records immediately for inspection by a Provincial Officer upon his or her request. The Permit Holder, unless otherwise required by the Director, shall submit, on or before March 31st in every year, the records required by this condition to the ministry's Water Taking Reporting System.
- 4.2 The Permit Holder shall monitor water levels at the following monitoring points as described below:

	Water Level Elevations		
Well No. /Pond Name	Continuous Datalogger (4-hour intervals)	Monthly Manuals	

Wash Pond (during unfrozen conditions)	X	X
OW2-A	X	X
OW2-B	X	X
OW2-C	X	X
OW3-A	X	X
OW3-B	X	X
OW4-A	X	X
OW4-B	X	X
OW4-C	X	X
OW5-A	X	X
OW5-B	X	X
OW5-C	X	X
OW6-A	X	X
OW7-A	X	X
OW7-C	X	X
OW8-A	X	X
OW8-B	X	X
OW9-A	X	X
OW10-A	X	X
OW10-B	X	X
OW11-A	X	X
OW11-C	X	X
OW12-A	X	X
OW13-A	X	X
North Pond	X	X
South Pond	X	X

4.3 The Permit Holder shall submit to the Director by March 31, 2019, a report with the monitoring data collected under Sections 4.1 and 4.2 of this Permit during the first two years of the aggregate washing operation, along with its interpretation; the report should include an assessment of the impact of the water taking, if any, on the surface water features (wetland) adjacent to the Wash Pond. The report should also include recommendations on modifications to the water taking and/or to the monitoring program as described in this Permit.

5. Impacts of the Water Taking

5.1 Notification

The Permit Holder shall immediately notify the local District Office of any complaint arising from the taking of water authorized under this Permit and shall report any action which has been taken or is proposed with regard to such complaint. The Permit Holder shall immediately notify the local District Office if the taking of water is observed to have any significant impact on the surrounding waters. After hours, calls shall be directed to the Ministry's Spills Action Centre at 1-800-268-6060.

5.2 For Groundwater Takings

If the taking of water is observed to cause any negative impact to other water supplies obtained from any adequate sources that were in use prior to initial issuance of a Permit for this water taking, the Permit Holder shall take such action necessary to make available to those affected, a supply of water equivalent in quantity and quality to their normal takings, or shall compensate such persons for their reasonable costs of so doing, or shall reduce the rate and amount of taking to prevent or alleviate the observed negative impact. Pending permanent restoration of the affected supplies, the Permit Holder shall provide, to those affected, temporary water supplies adequate to meet their normal requirements, or shall compensate such persons for their reasonable costs of doing so.

If permanent interference is caused by the water taking, the Permit Holder shall restore the water supplies of those permanently affected.

6. Director May Amend Permit

The Director may amend this Permit by letter requiring the Permit Holder to suspend or reduce the taking to an amount or threshold specified by the Director in the letter. The suspension or reduction in taking shall be effective immediately and may be revoked at any time upon notification by the Director. This condition does not affect your right to appeal the suspension or reduction in taking to the Environmental Review Tribunal under the *Ontario Water Resources Act*, Section 100 (4).

The reasons for the imposition of these terms and conditions are as follows:

- 1. Condition 1 is included to ensure that the conditions in this Permit are complied with and can be enforced.
- 2. Condition 2 is included to clarify the legal interpretation of aspects of this Permit.
- 3. Conditions 3 through 6 are included to protect the quality of the natural environment so as to safeguard the ecosystem and human health and foster efficient use and conservation of waters. These conditions allow for the beneficial use of waters while ensuring the fair sharing, conservation and sustainable use of the waters of Ontario. The conditions also specify the water takings that are authorized by this Permit and the scope of this Permit.

In accordance with Section 100 of the <u>Ontario Water Resources Act</u>, R.S.O. 1990, you may by written notice served upon me, the Environmental Review Tribunal and the Environmental Commissioner, **Environmental Bill of Rights**, R.S.O. 1993, Chapter 28, within 15 days after receipt of this Notice, require a hearing by the Tribunal. The Environmental Commissioner will place notice of your appeal on the Environmental Registry. Section 101 of the <u>Ontario Water Resources Act</u>, as amended provides that the Notice requiring a hearing shall state:

- 1. The portions of the Permit or each term or condition in the Permit in respect of which the hearing is required, and;
- 2. The grounds on which you intend to rely at the hearing in relation to each portion appealed.

In addition to these legal requirements, the Notice should also include:

AND

- a. The name of the appellant;
- b. The address of the appellant;
- c. The Permit to Take Water number;
- d. The date of the Permit to Take Water;
- e. The name of the Director:
- f. The municipality within which the works are located;

This notice must be served upon:

The Secretary
Environmental Review Tribunal
655 Bay Street, 15th Floor
Toronto ON
M5G 1E5

Fax: (416) 326-5370

Email:

ERTTribunalsecretary@ontario.ca

The Environmental Commissioner 1075 Bay Street 6th Floor, Suite 605 Toronto, Ontario, M5S 2W5

Toronto, Ontario M5S 2W5

The Director, Section 34.1,
Ministry of the Environment and
Climate Change
12th Floor
119 King St W

Hamilton ON L8P 4Y7 Fax: (905) 521-7820

Further information on the Environmental Review Tribunal's requirements for an appeal can be obtained directly from the Tribunal:

by Telephone at (416) 212-6349

Toll Free 1(866) 448-2248

by Fax at (416) 326-5370

Toll Free 1(844) 213-3474

by e-mail at

<u>AND</u>

www.ert.gov.on.ca

This instrument is subject to Section 38 of the **Environmental Bill of Rights** that allows residents of Ontario to seek leave to appeal the decision on this instrument. Residents of Ontario may seek to appeal for 15 days from the date this decision is placed on the Environmental Registry. By accessing the Environmental Registry, you can determine when the leave to appeal period ends.

Dated at Hamilton this 8th day of May, 2017.

Belinda Koblik

Director, Section 34.1

Ontario Water Resources Act, R.S.O. 1990

Schedule A

This Schedule "A" forms part of Permit To Take Water 3210-AKRL9C, dated May 8, 2017.

- 1. Hydrogeological Assessment in Support an OWRA Sec 34 PTTW, Shelburne South Pit, dated December, 2016, prepared by Whitewater Hydrogeology Ltd. for Strada Aggregates.
- 2. 2016 Compliance Groundwater Monitoring Report, Shelburne South Pit, dated January 2017, prepared by Whitewater Hydrogeology Ltd. for Strada Aggregates.

Appendix B: Integrated Monitoring Plan

Strada Aggregates Melancthon Pits – Integrated Monitoring Plan February 2018

Background

The Strada Melancthon Pits consist of:

- Pit #1 (Licence # 129167) located at West Half of Lot 13, Concession 3 O.S., licenced in 2004;
- Pit #2 (Licence # 625155) located at West Half of Part Lot 11 and 12, Concession 3 O.S., licenced in 2012; and
- The proposed Bonnefield and Prince extension lands located at Part of West Half of Lots 12 and 14, Concession 3 O.S.

The proposed Prince and Bonnefield extensions will be fully integrated with existing aggregate operations at Melancthon Pits #1 and #2. The existing operations require monitoring and annual reporting with respect to the water table, water quality and the natural environment. Hydrogeological and natural environment investigations for the proposed extension have recommended expansion of the monitoring programs to include the additional lands. The Ministry of Natural Resources and Forestry (MNRF) has requested an Integrated Monitoring Plan to consolidate the existing and proposed monitoring requirements.

Natural Environment

Amphibian Monitoring

Annual monitoring of the wetlands for the presence of breeding amphibians was originally recommended in the Level 2 Natural Environment Assessment (NEA) report for Melancthon Pit #2, as well as surface and groundwater monitoring to assess water level fluctuations (NRSI 2010). The implementation of an amphibian monitoring program was further requested by the Nottawasaga Valley Conservation Authority (NVCA) and Michalski Nielson in their review of the Level 2 NEA report.

NRSI has undertaken annual amphibian monitoring at the wetlands located adjacent to Melancthon Pit #2 since 2013. Initial amphibian call surveys were undertaken in 2009.

Of the two proposed pit areas, only the Bonnefield Pit property contains wetland habitat (outside the extraction area). Surveys completed in 2016 recorded the presence of breeding amphibians. To ensure that the proposed pit does not negatively impact the wetland and its amphibian breeding habitat function it was recommended that the existing amphibian monitoring program for Melancthon Pit #2 be expanded to include the Bonnefield Pit to maximize efficiencies, and achieve consistency in methodology and data comparability.

Annual amphibian call surveys that were initiated at Melancthon Pit #2 will continue for the duration of the lifespan of the pit, as was originally proposed. Beginning in 2018, NRSI will initiate annual monitoring of the Bonnefield property wetland which will also be undertaken for the lifespan of that pit. Annual monitoring of the Bonnefield Pit wetland will build on NRSI's 2016 amphibian call surveys on the property

to inform the NEA report. See **Map 1** for the location of the existing monitoring stations at Melancthon Pit #2 in addition to the single monitoring station at the Bonnefield Pit wetland. Since no amphibian calling activity was documented within the Bonnefield property vernal pool during 2016 surveys, despite the presence of standing water, additional long-term monitoring of the vernal pool is not included in this plan. However, if amphibian calling activity is heard within the vernal pool during future monitoring years, an additional monitoring station will be established at this location and will be monitored annually.

Proposed monitoring at the Bonnefield Pit wetland will document additional baseline data on breeding amphibian species presence and relative abundance prior to aggregate extraction, followed by multiple years of operational-stage monitoring. As has been completed for Melancthon Pit #2, long-term data will be collected to identify trends or other indicators that will be used to assess any negative occurrences to amphibian breeding activity that may be the result of pit activities. The amphibian survey data collected at the Bonnefield and Melancthon Pit #2 sites will also be compared to look for spatial trends, or any similarities or differences in survey results over time that may indicate presence of localized or widespread pit operation effects.

In accordance with survey methodology completed to date, the monitoring program will utilize the Marsh Monitoring Program methodology (BSC 2009), which records amphibian call activity during 3-minute call counts. Counts will be conducted once per month during each of April, May and June in conjunction with appropriate night time air temperatures and wind speeds. If the provincial Species of Conservation Concern Western Chorus Frog (Pseudacris triseriata) is detected during any monitoring event, additional monitoring events may be added to fully document the abundance and distribution of this species within the surveyed wetlands.

A brief summary report, combining the results collected from the Melancthon Pit #2 site with the Bonnefield Pit site, will be prepared each year which outlines the findings of the annual monitoring. This will include an assessment of the surface water and groundwater monitoring data to be collected by Whitewater Hydrogeology within both properties (Whitewater Hydrogeology 2017) as it relates to amphibian breeding conditions. Each annual report will be provided to Strada for their review, and then to the NVCA and the Township of Melancthon.

Woodland Buffer

The deciduous woodland communities within the Bonnefield and Prince extension lands will be retained outside the proposed limit of extraction. 10 metre woodland buffers have been recommended to protect these features and mitigate impacts from adjacent extraction activities. The woodland buffers will be allowed to re-naturalize and will be supplemented with targeted native species plantings.

The woodland buffers will be inspected during pit operations to ensure disturbances are not occurring. The health and survival of buffer planting will also be inspected.

Hydrogeology

Compliance groundwater and surface water monitoring has been occurring at both Melancthon Pit #1 and #2 since 2001 and 2007, respectively. In addition, baseline groundwater monitoring commenced in

2017 at the Bonnefield and Prince properties. In total, there are currently 28 groundwater well nests that monitor 52 discrete aquifer intervals in the overburden and bedrock aquifers. The Melancthon Pit #1 and #2 groundwater monitoring programs were developed to characterize the local groundwater conditions at each individual property and were based on two operating pits (two scale houses, two fuel storage areas, and multiple crushing and processing operations). The proposed licensing of the Bonnefield and Prince properties provides an opportunity to not only streamline operations by eliminating the need to operate as individual pits but to develop a revised groundwater monitoring program. The revision would remove redundancies in the monitoring network and reporting allowing for an opportunity to complete an accumulative impact assessment from the Strada properties.

The revised groundwater monitoring program is shown on **Map 2**. The revised program consists of 22 groundwater well nests that monitor 36 discrete aquifer intervals in the overburden and bedrock aquifers.

The proposed program focuses on the on going monitoring of background conditions (up gradient locations) in both the overburden and bedrock aquifers and the monitoring of potential influences from the aggregate operation on down gradient locations. The proposed groundwater monitoring program is provided in **Table 1**. Selected up gradient and down gradient wells will be sampled for water quality. The water quality parameters for the semi annual (spring and fall) and annual (spring) sampling programs are provided in **Table 2**.

Surface water elevation monitoring has been on-going at the North and South Ponds (Map 2), since 2007. Two additional surface water monitoring stations to monitor the hydro-period in the wetland and vernal pool (Map 2) will commence in 2018. This monitoring will consist of the collection of continuous water level data during non-frozen conditions. Data will be assessed in conjunction with the groundwater monitoring data as part of the annual reporting requirement.

Table 1 – Proposed Groundwater Monitoring Network

Well ID	Water Levels	Water Quality				
	Monthly Manual Water	Semi-Annual	Annual			
OW2-A	X	X				
OW2-B	X	X				
OW3-B	X	X				
OW4-A	X	X				
OW4-B	X	X				
OW5-A	X	X	X			
OW5-B	X	X				
OW6-A	X	X	X			
OW7-A	X	X	X			
OW7-B	X	X				
OW8-A	X	X	X			
OW9-A	X	X	X			
OW10-A	X	X	X			
OW11-A	X	X	X			
OW11-B	X	X				
OW12-A	X	X	X			

Well ID	Water Levels	Water Quality			
	Monthly Manual Water	Semi-Annual	Annual		
OW13-A	X	X			
OW13-B	X	X			
OW14-B	X	X	X		
OW15-B	X				
OW16-B	X	X	Х		
OW17-A	X				
OW17-B	X				
OW18-A	X	X	Х		
OW18-B	X	X			
OW19-A	X				
OW19-B	X	X			
OW20-B	X	X	X		
OW21-B	X	X	x		
OW22-B	X	X			
OW23-B	X	X			

Note: the collection of continuous water levels at selected groundwater monitoring locations is recommended.


Table 2 – Proposed Water Quality Parameters

Semi-Annual Groundwater Quality Parameters	Annual Groundwater Quality Parameters
General Water Quality Parameters: pH, Conductivity, Alkalinity, Bicarbonate, Chloride, Calcium, Magnesium, Potassium, Sodium, Sulphate, Nitrate, Nitrite, Phosphorous, and Metals (dissolved).	BTEX, Total Oil and Grease

It is recommended that a single annual groundwater monitoring report for the Melancthon Pits #1 and 2, as well as the proposed Bonnefield and Prince Pits be prepared and submitted to the MNRF, Township of Melancthon and NVCA prior to March 31st of each year and include the monitoring data for the 12 month period ending December 31st of the previous year. The report shall include, but not be limited to, the following:

- 1. Monitoring data collected as per Table 1 and Table 2;
- 2. Data in tabulated and graphical formats;
- 3. Interpretation of the collected data including discussions of any observed trends in groundwater levels and groundwater quality (analytical) results;
- 4. Recommendations on and justification for the need for make changes to monitoring locations, monitoring frequency, type of monitoring, pumping patterns and/or the need for mitigation, and
- 5. Summary and documentation of any water well complaint(s) and their resolution(s).





560800 m 561000 m 561200 m 561400 m 561600 m 561800 m 562000 m 562200 m 562400 m 562600 m 562800 m 563000 m 563200 m

Appendix C: Borehole Logs

Figure A.17: New Borehole log for Well OW3.





Figure A.19: New Borehole log for Well OW4.





Figure A.21: Updated Borehole log for Well OW5.





Figure A.22: Borehole log for Well OW6-A.





Figure A.23: Borehole log for Well OW7 A and C.





Figure A.24: Borehole log for Well OW8.





Figure A.26: New Borehole log for Well OW9-A.





Figure A.28: New Borehole log for Well OW10.





Figure A.29: Borehole log for Well OW11 A and C.





The Environment of the Environme	Well Tag No. (Place S	A 047149	Regulation 903 (Well Re	urces Act
Well Owner's Information					25 40
First Name Last Nam STRADA AGGREGATES	ne E-n	nail Address		☐ Well Cons by Well C	structed Owner
Mailing Address (Street Number/Name, RR)	Municipality	Province	Postal Code	Telephone No. (inc. ai	
30 FLORAL PARKWAY Part A Construction and/or Major Alters	CONCORD	ONT	L4K 4R1		
Address of Well Location (Street Number/Name	e, RR) Township		Lot	Concession	
County/District/Municipality	MELAN City/Town/Villa		11 Provi	3 nce Postal 0	Code
DUFFERIN			Ont	ario	
	orthing GPS Unit Make 4887189 GARMIN		Operation: Undifficientiated, specify	erentiated X Aver	aged
Overburden and Bedrock Materials (see ins				Self-treats	B/03/2
General Colour Most Common Material	Other Materials	General C	Description	From	Metres) To
BROWN SAND & GRAVEL				0	25ft
BROWN SILTY CLAY & S				25ft	37ft
GRAY CLAY GRAVEL	AERS			37ft 69	69ft 71ft
GRAY LIMESTONE				0,7	7110
	2in PVC				
	10ft screen bot	tom 69ft			
	10ft screen bot				
	onment Sealing Record	STATE OF THE STATE	Results of Well Yie		Section.
Depth Set at (Metres) Type of Set From To (Material s	ealant Used Volume and Type) (Cubic	Check box if after ter water was:	Time	Water Level Time V	Vater Level
O 14ft BENTONIT	E	☐ Cannot develop		Static	(Metres)
		state If pumping disconting	ued, give reason:	Level 1	
		Dumping tost math		2	
		Pumping test method	3	3	
Method of Construction	Water Use	Pump intake set at	(Metres)	4	
		Not used Dewatering Pumping rate (Litre		5	
☐ Rotary (Reverse) ☐ Driving ☐ ☐ L	ivestock Test Hole Tight	Monitoring Duration of pumpin		10	
☐ Air percussion ☐ Boring ☐ In	ndustrial	hrs +	min 15		
	Other, specify	Final water level end (Metres)	of pumping 20	20	
☐ Water Supply ☐ Dewatering Well ☐ Replacement Well ☐ Abandoned, Insuffic	Observation and/or More ient Supply Alteration (Construction	Recommended pui	mp type		
☐ Test Hole ☐ Abandoned, Poor W	/ater Quality Other, specify	Shallow Recommended pur	Deep		
	on of Well	Metre	10	40	
Please provide a map below showing: - all property boundaries, and measurements suffic		Recommended pur (Litres/min)	mp rate 50		
an arrow indicating the North direction detailed drawings can be provided as attachments.		If flowing give rate (Litres/min)	60		
 vidigital pictures of inside of well can also be provi 	ided				
1 Cl#	XWELC	Water found at De		ter	
	8#	Water found at D			Minerals
100		Metres	Gas Fresh	Salty Sulphur	Minerals
, , ,		Water found at D		ter Salty Sulphur	Minerals
D 1		Casing Used	Screen Used	Casing and Well I	
Jest .		Galvanized	Galvanized	Nameter of the Hole (Cer.	
* 1	Loc	Steel	Steel C	6 in Depth of the Hole (Metres	,
Date Well Completed Was the well owner's info package delivered?	ormation Date the Well Record and Pa Delivered to Well Owner (yy)	ckage Plastic Concrete	C Plastic V	71ft Vall Thickness (Metres)	
2008/4/122 Yes	s No		nd Screen Head		
Well Contractor and Well Business Name of Well Contractor	ell Technician Information Well Contractor's L	C Occa Hala	lr.	nside Diameter of the Ca	sing (Metres)
KEITH LANG WELL DRILLI		Disinfected?	C	Depth of the Casing (Metr	res)
Business Address (Street No./Name, number, R 251 ELDON ST GODERICH		Yes No	Ministry Use	Only	
Province Postal Code Busine	ess E-mail Address	Audit No. z 69	Well	Contractor No.	
ONT N7A 3R9 Bus.Telephone No. (inc. area code) Name of Well	Technician (Last Name, First Name)	Date Received (1995)		of Inspection (yyyy/mm/c	(d)
519-524-8159 K Well Technician's Licence No. Signature of Technic		JUNU	D ZUUB		10 300
Well Technician's Licence No. Signature of Technology	Date Submitted (yyyy/mm/dd) Remarks			
0506E (11/2006)	Ministr	ry's Copy		© Queen's Printer for	Ontario, 2006

Figure A.30: Borehole log for Well OW12.





Figure A.31: Borehole log for Well OW13 A and B.





Figure A.32: Updated Borehole log for Well OW14 A and C.





Figure A.33: Borehole log for Well OW15.





()	ntario	Ministr the En	ry of vironment		Well Ta	g No. (Pla	A1	15091	Regulation	903 O	ntario Wa	er Res	
	ents record		letric 🔲	mperial		Cit Immobiliano di Salakistro	CONTRACTOR OF THE STATE OF THE	Name and the same		seans voige	Page_	ADMINISTRA	of
Well Owl	ner's Info		ast Name / 0	Organization	1			E-mail Ac	ldress		Iг) Well C	Constructed
STR		GERAGA	TES						Postal Code		elephone N	by We	ll Owner
		t Number/Nar PARKWAY	ne)		10	Municipality CONCOR	n	Province ONT			elephone i	io. (mc. i	area code)
Well Loca		AKKWAI				CONCOR	D	1 0111					
		on (Street Nur	nber/Name)	- Control of the Cont	1	Township MELANC	THON		Lot 13	(Concession 3	1	
County/Dis	trict/Munici	nality				City/Town/Villag			13	Provinc	e	Postal	Code
	I	UFFERI								Onta	rio		
	inates Zone			orthing 488799		Municipal Plan	and Subic	ot Number		Other			
Overburd	0 3	1 1 1 1	1 i I	nment Sea	iling Reco	ord (see instruct	tions on the	back of this for	n)				
General C	olour	Most Comn	non Material		Oth	ner Materials			General Description			From	h (m/ft) To
BROW	N S	SAND &	GRAVEL								- 1	0 Oft	20ft 37ft
BROWN	I	IMESTO	NE SOF	T								.016	3710
		******											-

													-
							and the same party	Lower and the contract of	70)	II WELL	14-11-1	NOSS (Records)	9800 0200 0000
Depth S	et at (m/ft)		Annular Type of Sea			Volume F	Placed		Results of We ell yield, water was:	Dra	w Down		ecovery
From	То		(Material ar	id Type)		(m³/fi		☐ Clear an ☐ Other, s		Time (min)	Water Leve (m/ft)	(min)	Water Level (m/ft)
0	25ft	BEN	TONITE	971	BAGS				continued, give reason:	Static Level			
										1		1	
								Pump intake	set at (m/ft)	2		2	
									41 1 40010	3		3	
Met	hod of Co	nstruction	legis (Carlo		Well U			Pumping rate	(I/min / GPM)	4		4	
Cable To	ool Conventional	☐ Diamono ☐ Jetting		blic mestic	Comme		lot used lewatering	Duration of p		5		5	
Rotary (Reverse)	☐ Driving	Liv	estock	☐ Test Ho		Monitoring	hrs +	min vel end of pumping (m/fl)	III	***************************************	+-+	
☐ Boring ☐ Air percu	ussion	Digging Digging	☐ Inc	gation fustrial	[] Cooking	a All Collation	ing	I ma naior io	or error or peroperation of	10		10	
Other, s				her, specify	10 E.S. 10 FOR 1991	Status o	£141210000	If flowing give	rate (l/min / GPM)	15		15	
Inside	Open Hol	nstruction R e OR Material	ecord - Ca		n (m/ft)	☐ Water Su		Recommend	ed pump depth (m/ft)	20	****	20	
Diameter (cm/in)	(Galvaniza Concrete,	ed, Fibreglass, Plastic, Steel)	Thickness (cm/in)	From	То	Replacen Test Hole		NAMES TO ADMINISTRATION OF THE PARTY OF THE		25		25	
2in	plas	tic	40	0	26ft	. Recharge	Well	(Vmin / GPM)	ed pump rate	30		30	
	ļ -					Dewaterir Observati	on and/or	Well product	ion (l/min / GPM)	40		40	
AND DESCRIPTION OF THE PERSON	-					Monitoring Alteration				50		50	
						(Construc		Disinfected?	No	60		60	
5.00,000,000	C	onstruction R	ecord - Scr	en		Insufficier Abandone	nt Supply		Map of W	ell Loc	ation		
Outside Diameter	N	laterial	Slot No.	Depti	h (<i>m/ft</i>)	Water Qu	ality	Please provid	e a map below following	instructi	ons on the	oack.	
(cm/in)	(Plastic, Ge	lvanized, Steel)		From	То	specify	ca, caror,	11471					1
211	pla	stic	.10	26ft	36ft	Other, sp	ecify		SCALE	Hou	isil	1	N
												,	
100000000000000000000000000000000000000	ad at Dooth	Water De Kind of Water		Untested	-	Hole Diamete	Diameter		 		5	tap	
354+		Other, sp		Onteated	From	То	(cm/in)		LANE			RI	T
Water four	nd at Depth	Kind of Wate	r: Fresh	Untested	0	37ft	6in					ŧ	
Water for	n/ft) Gas	Other, spe Kind of Wate	ecify Fresh	Untested							X	WE	L.C.
		Other, sp									, -	,	- •
		ell Contract	or and Wel	Technicia	ın Informa	ation /ell Contractor's L	icence No]]]			i		
KEITI	lame of We LANG	Contractor WELL I	ORILLI	NG INC		7154	icance No.					,	
		eet Number/N			М	unicipality		Comments:					
251 I Province		ST GODI Postal Code		s E-mail Add	dress			-					
		N7A3R9						Well owner's	Date Package Deliver	ed	Mini	stry Us	e Only
ONT	Ľ							information					
ON T Bus.Teleph	one No. (inc.	area code) N				, First Name)		information package delivered	YYYYMM		Audit No.	142	2139
Bus.Teleph Well Techni	ione No. (inc.	area code) N No. Signature	KEI	TH LAN	IG ontractor D		. 1 .	package	Y Y Y M M Date Work Completed 2012 6 2		Audit No. Z AUI	142 316	2139

Figure A.34: Borehole log for Well OW16C.





Figure A.35: Borehole log for Well OW17.





Figure A.36: Borehole log for Well OW18.





Figure A.37: Borehole log for Well OW19.





Figure A.38: Borehole log for Well OW20.





Figure A.39: Borehole log for Well OW21.





Figure A.40: Borehole log for Well OW22.







Figure A.41: Borehole log for Well OW23.








Appendix D: Hydrographs













































































Appendix E: Water Quality Results



CERTIFICATE OF ANALYSIS

Final Report

REPORT No: 23-005120 - Rev. 2 C.O.C.: G106186

Report To:

Tatham Engineering 115 Sandford Fleming Drive Suite 200

Collingwood, ON L9Y 5A6

Attention: Alicia Kimberley

DATE RECEIVED:

Barrie, ON L4N 8W8

112 Commerce Park Dr Unit L

CADUCEON Environmental Laboratories

CUSTOMER PROJECT: Strada - Shelburne

123016

2024-Mar-12 P.O. NUMBER:

DATE REPORTED: **Ground Water** SAMPLE MATRIX:

2023-Mar-22

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	4	OTTAWA	VKASYAN	2023-Mar-24	A-IC-01	SM 4110B
Cond/pH/Alk Auto (Liquid)	4	OTTAWA	SBOUDREAU	2023-Mar-24	COND-02/PH-02/A	SM 2510B/4500H/
					LK-02	2320B
ICP/MS (Liquid)	4	OTTAWA	TPRICE	2023-Mar-28	D-ICPMS-01	EPA 200.8
ICP/OES (Liquid)	4	OTTAWA	NHOGAN	2023-Mar-28	D-ICP-01	SM 3120B
Oil & Grease (Liquid)	3	KINGSTON	MTYMCHUK	2023-Mar-27	O&G-001	SM 5520
PHC F1 (Liquid)	3	RICHMOND_HILL	JEVANS	2023-Mar-25	C-VPHW-01	MECP E3421
PHC F2-4 (Liquid)	3	KINGSTON	KPARKER	2023-Mar-24	PHC-W-001	MECP E3421
VOC-Volatiles Full (Water)	3	RICHMOND_HILL	JEVANS	2023-Mar-25	C-VOC-02	EPA 8260

μg/g = micrograms per gram (parts per million) and is equal to mg/Kg

F1 C6-C10 hydrocarbons in $\mu g/g$, (F1-btex if requested)

F2 C10-C16 hydrocarbons in µg/g, (F2-napth if requested)

F3 C16-C34 hydrocarbons in $\mu g/g$, (F3-pah if requested)

F4 C34-C50 hydrocarbons in µg/g

This method complies with the Reference Method for the CWS PHC and is

validated for use in the laboratory.

Any deviations from the method are noted and reported for any particular sample.

nC6 and nC10 response factor is within 30% of response factor for toluene:

nC10,nC16 and nC34 response factors within 10% of each other:

C50 response factors within 70% of nC10+nC16+nC34 average:

Linearity is within 15%:

All results expressed on a dry weight basis.

Unless otherwise noted all chromatograms returned to baseline by the retention

time of nC50.

R.L. = Reporting Limit

NC = Not Calculated

Test methods may be modified from specified reference method unless indicated by an *

Unless otherwise noted all extraction, analysis, QC requirements and limits for holding time were met. If analyzed for F4 and F4G they are not to be summed but the greater of the two numbers are to be used in application to the CWS PHC

QC will be made available upon request.

Final Report REPORT No: 23-005120 - Rev. 2

							REPORT No: 2	3-005120 - Rev. 2
				Client I.D.	OW 18 - C	OW 18 - A	OW 14 - C	OW 16 - C
				Sample I.D.	23-005120-1	23-005120-2	23-005120-3	23-005120-4
				Date Collected	2023-Mar-22	2023-Mar-22	2023-Mar-22	2023-Mar-22
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	207	205	416	121
Bicarbonate (as CaCO3)	mg/L as CaCO3	5			207	205	416	121
pH @25°C	pH units	-	8.5	OG	7.76	7.79	7.65	7.44
Conductivity @25°C	uS/cm	1			444	443	820	273
Chloride	mg/L	0.5	250	AO	6.1	6.1	2.9	4.7
Nitrate (N)	mg/L	0.05	10.0	MAC	1.48	1.44	3.71	0.87
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	7	8	7	7
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	223	237	418	130
Aluminum	mg/L	0.01	0.1	OG	0.03	0.03	0.08	0.02
Barium	mg/L	0.001	1	MAC	0.039	0.045	0.099	0.026
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.007	0.007	0.006	<0.005
Calcium	mg/L	0.02			65.7	70.5	111	39.9
Iron	mg/L	0.005	0.3	AO	<0.005	0.016	0.043	0.012
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			14.3	14.8	34.3	7.43
Manganese	mg/L	0.001	0.05	AO	0.001	0.002	0.006	0.003
Phosphorus	mg/L	0.1			<0.1	<0.1	<0.1	<0.1
Potassium	mg/L	0.1			0.7	0.7	0.8	1.1
Silicon	mg/L	0.01			1.68	1.67	2.69	0.84

Final Report REPORT No: 23-005120 - Rev. 2

							REPORT No: 2	3-005120 - Rev. 2
				Client I.D.	OW 18 - C	OW 18 - A	OW 14 - C	OW 16 - C
				Sample I.D.	23-005120-1	23-005120-2	23-005120-3	23-005120-4
				Date Collected	2023-Mar-22	2023-Mar-22	2023-Mar-22	2023-Mar-22
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			3.60	3.57	5.76	1.80
Sodium	mg/L	0.2	200, 20	AO, MAC	2.1	2.0	2.1	3.4
Strontium	mg/L	0.001			0.089	0.091	0.183	0.060
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	<0.005	0.044	0.007
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	0.0007	0.0002	<0.0001	0.0003
Arsenic	mg/L	0.0001	0.01	MAC	0.0002	0.0001	0.0002	0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	0.000022	<0.000015	0.000043	0.000019
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Cobalt	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Copper	mg/L	0.0001	1	AO	0.0016	0.0013	0.0006	0.0010
Lead	mg/L	0.00002	0.010	MAC	0.00010	0.00005	0.00026	<0.00002
Molybdenum	mg/L	0.0001			0.0001	0.0001	<0.0001	0.0004
Nickel	mg/L	0.0002			0.0002	0.0004	0.0007	<0.0002
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

				Client I.D.	OW 18 - C	OW 18 - A	OW 14 - C	OW 16 - C
				Sample I.D.	23-005120-1	23-005120-2	23-005120-3	23-005120-4
				Date Collected	2023-Mar-22	2023-Mar-22	2023-Mar-22	2023-Mar-22
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00015	0.00015	0.00016	0.00016
Vanadium	mg/L	0.0001			0.0002	0.0001	<0.0001	<0.0001
				Client I.D.	OW 18 - A	OW 14 - C	OW 16 - C	
				Sample I.D.	23-005120-2	23-005120-3	23-005120-4	_
				Date Collected	2023-Mar-22	2023-Mar-22	2023-Mar-22	-
Parameter	Units	R.L.	Limits	DWG	-	-	-	
Benzene	μg/L	0.5	1	MAC	<0.5	<0.5	<0.5	
Ethylbenzene	μg/L	0.5	140, 1.6	MAC, AO	<0.5	<0.5	<0.5	
Toluene	μg/L	0.5	60	MAC	<0.5	<0.5	<0.5	
Xylene, m,p-	μg/L	1			<1	<1	<1	
Xylene, m,p,o-	μg/L	1.1	90, 20	MAC, AO	<1.1	<1.1	<1.1	
Xylene, o-	μg/L	0.5			<0.5	<0.5	<0.5	
PHC F1 (C6-C10)	μg/L	25			<25	<25	<25	
PHC F2 (>C10-C16)	μg/L	50			<50	<50	<50	
PHC F3 (>C16-C34)	μg/L	400			<400	<400	<400	
PHC F4 (>C34-C50)	μg/L	400			<400	<400	<400	
Oil & Grease (Total)	mg/L	1.0			1.8	3.0	2.8	

Revised report to update sample ID's as per client request

DWG - Drinking Water Guidelines

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective

OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

Operational Guidelines							
OW 18 - C	Found Value	Limit					
Hardness (as CaCO3)	223	100					
OW 18 - A	Found Value	Limit					
Hardness (as CaCO3)	237	100					
OW 14 - C	Found Value	Limit					
Hardness (as CaCO3)	418	100					
OW 16 - C	Found Value	Limit					
Hardness (as CaCO3)	130	100					



CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: G106189 REPORT No: 23-005262 - Rev. 1

Report To:

Tatham Engineering 115 Sandford Fleming Drive

Suite 200

Collingwood, ON L9Y 5A6

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8

Attention: Alicia Kimberley

DATE REPORTED:

DATE RECEIVED: 2023-Mar-24

CUSTOMER PROJECT: Strada - Shelburne

P.O. NUMBER:

2024-Mar-12 123016

Ground Water SAMPLE MATRIX:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	2	OTTAWA	PCURIEL	2023-Mar-29	A-IC-01	SM 4110B
Cond/pH/Alk Auto (Liquid)	2	OTTAWA	SBOUDREAU	2023-Mar-28	COND-02/PH-02/A	SM 2510B/4500H/
					LK-02	2320B
ICP/MS (Liquid)	2	OTTAWA	TPRICE	2023-Mar-30	D-ICPMS-01	EPA 200.8
ICP/OES (Liquid)	2	OTTAWA	NHOGAN	2023-Mar-29	D-ICP-01	SM 3120B

R.L. = Reporting Limit

NC = Not Calculated

Test methods may be modified from specified reference method unless indicated by an *

REPORT No: 23-005262 - Rev. 1

				Client I.D.	OW 13-A	OW 13-C
Parameter	Units	R.L.	Limits	Sample I.D. Date Collected DWG	23-005262-1 2023-Mar-22	23-005262-2 2023-Mar-22
		5 S	500	OG	248	275
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	240	2/5
Bicarbonate (as CaCO3)	mg/L as CaCO3	5			248	275
pH @25°C	pH units	-	8.5	OG	7.63	7.56
Conductivity @25°C	uS/cm	1			571	596
Chloride	mg/L	0.5	250	AO	12.1	10.1
Nitrate (N)	mg/L	0.05	10.0	MAC	1.37	1.68
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05
Sulphate	mg/L	1	500	AO	19	7
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	279	305
Aluminum	mg/L	0.01	0.1	OG	0.05	0.07
Barium	mg/L	0.001	1	MAC	0.037	0.040
Bismuth	mg/L	0.02			<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.007	0.007
Calcium	mg/L	0.02			78.8	88.7
Iron	mg/L	0.005	0.3	AO	0.027	0.016
Lithium	mg/L	0.005			<0.005	<0.005
Magnesium	mg/L	0.02			20.0	20.2
Manganese	mg/L	0.001	0.05	AO	0.028	0.007
Phosphorus	mg/L	0.1			<0.1	<0.1
Potassium	mg/L	0.1			1.2	1.3
Silicon	mg/L	0.01			2.60	2.43

REPORT No: 23-005262 - Rev. 1

				Client I.D.	OW 13-A	OW 13-C
December	Units	D.	Limite	Sample I.D. Date Collected DWG	23-005262-1 2023-Mar-22	23-005262-2 2023-Mar-22
Parameter Silica	Units mg/L	R.L. 0.02	Limits	DWG	5.56	5.20
Sodium	mg/L	0.2	200, 20	AO, MAC	11.8	6.7
Strontium	mg/L	0.001			0.119	0.115
Tin	mg/L	0.05			<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	0.010
Zirconium	mg/L	0.003			<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	0.0006	0.0002
Beryllium	mg/L	0.0001			<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	0.000015	<0.000015
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001
Cobalt	mg/L	0.0001			0.0003	0.0002
Copper	mg/L	0.0001	1	AO	0.0016	0.0011
Lead	mg/L	0.00002	0.010	MAC	0.00005	0.00007
Molybdenum	mg/L	0.0001			0.0002	0.0001
Nickel	mg/L	0.0002			0.0004	0.0003
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005

Final Report

REPORT No: 23-005262 - Rev. 1

				Client I.D.	OW 13-A	OW 13-C
				Sample I.D.	23-005262-1	23-005262-2
				Date Collected	2023-Mar-22	2023-Mar-22
Parameter	Units	R.L.	Limits	DWG	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00032	0.00025
Vanadium	mg/L	0.0001			0.0002	<0.0001

Revised report to update sample ID's as per client request

DWG - Drinking Water Guidelines

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective

OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

Summary of Exceedances		
Operational Guidelines		
OW 13-A	Found Value	Limit
Hardness (as CaCO3)	279	100
OW 13-C	Found Value	Limit
Hardness (as CaCO3)	305	100



Client committed, Quality assured, Canadian owned,

CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: G106193-4 REPORT No: 23-005581 - Rev. 1

Report To:

Tatham Engineering 115 Sandford Fleming Drive

Suite 200

Collingwood, ON L9Y 5A6

Attention: Alicia Kimberley

DATE RECEIVED: 2023-Mar-28 DATE REPORTED: 2024-Mar-12

SAMPLE MATRIX: Ground Water

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L Barrie, ON L4N 8W8

CUSTOMER PROJECT: 123016

P.O. NUMBER:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	16	OTTAWA	PCURIEL	2023-Mar-30	A-IC-01	SM 4110B
Cond/pH/Alk Auto (Liquid)	16	OTTAWA	SLOZO	2023-Mar-30	COND-02/PH-02/A	SM 2510B/4500H/
					LK-02	2320B
ICP/MS (Liquid)	16	OTTAWA	TPRICE	2023-Mar-30	D-ICPMS-01	EPA 200.8
ICP/OES (Liquid)	16	OTTAWA	NHOGAN	2023-Mar-31	D-ICP-01	SM 3120B
Oil & Grease (Liquid)	9	KINGSTON	MTYMCHUK	2023-Mar-31	O&G-001	SM 5520
PHC F1 (Liquid)	9	RICHMOND_HILL	FLENA	2023-Mar-31	C-VPHW-01	MECP E3421
PHC F2-4 (Liquid)	9	KINGSTON	KPARKER	2023-Mar-31	PHC-W-001	MECP E3421
VOC-Volatiles Full (Water)	9	RICHMOND_HILL	FLENA	2023-Apr-01	C-VOC-02	EPA 8260

 $\mu g/g$ = micrograms per gram (parts per million) and is equal to mg/Kg

F1 C6-C10 hydrocarbons in $\mu g/g$, (F1-btex if requested)

F2 C10-C16 hydrocarbons in $\mu g/g$, (F2-napth if requested)

F3 C16-C34 hydrocarbons in µg/g, (F3-pah if requested)

F4 C34-C50 hydrocarbons in µg/g

This method complies with the Reference Method for the CWS PHC and is

validated for use in the laboratory.

Any deviations from the method are noted and reported for any particular sample.

nC6 and nC10 response factor is within 30% of response factor for toluene:

nC10,nC16 and nC34 response factors within 10% of each other:

C50 response factors within 70% of nC10+nC16+nC34 average:

Linearity is within 15%:

All results expressed on a dry weight basis.

Unless otherwise noted all chromatograms returned to baseline by the retention

time of nC50.

R.L. = Reporting Limit

NC = Not Calculated

Test methods may be modified from specified reference method unless indicated by an *

Unless otherwise noted all extraction, analysis, QC requirements and limits for holding time were met. If analyzed for F4 and F4G they are not to be summed but the greater of the two numbers are to be used in application to the CWS PHC

QC will be made available upon request.

REPORT No: 23-005581 - Rev. 1

							ILLI OILI IIO. 2	.3-005561 - Rev. 1
				Client I.D.	OW 9A	OW 12A	OW 6A	OW 8A
				Sample I.D.	23-005581-1	23-005581-2	23-005581-3	23-005581-4
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	329	191	216	292
Bicarbonate (as CaCO3)	mg/L as CaCO3	5			329	191	216	292
pH @25°C	pH units	-	8.5	OG	7.88	8.02	8.04	7.91
Conductivity @25°C	uS/cm	1			833	365	510	776
Chloride	mg/L	0.5	250	AO	24.5	1.8	11.4	43.1
Nitrate (N)	mg/L	0.05	10.0	MAC	17.3	1.76	0.82	14.8
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	18	5	37	9
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	413	190	249	380
Aluminum	mg/L	0.01	0.1	OG	0.08	0.05	0.02	0.06
Barium	mg/L	0.001	1	MAC	0.073	0.007	0.061	0.109
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.008	0.008	0.016	0.005
Calcium	mg/L	0.02			131	67.0	70.3	103
Iron	mg/L	0.005	0.3	AO	<0.005	0.025	0.005	<0.005
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			20.7	5.57	17.8	29.7
Manganese	mg/L	0.001	0.05	AO	0.005	0.003	0.005	<0.001
Phosphorus	mg/L	0.1			<0.1	<0.1	<0.1	<0.1
Potassium	mg/L	0.1			1.0	1.3	2.3	1.1
Silicon	mg/L	0.01			3.22	1.74	1.68	3.77

Final Report REPORT No: 23-005581 - Rev. 1

							REPURI NO: 2	3-005581 - Rev. 1
				Client I.D.	OW 9A	OW 12A	OW 6A	OW 8A
				Sample I.D.	23-005581-1	23-005581-2	23-005581-3	23-005581-4
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG		-	-	-
Silica	mg/L	0.02			6.89	3.72	3.60	8.07
Sodium	mg/L	0.2	200, 20	AO, MAC	2.7	1.0	5.3	8.9
Strontium	mg/L	0.001			0.195	0.149	0.154	0.177
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	0.005	<0.005	<0.005	<0.005
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	0.000018	<0.000015	<0.000015	<0.000015
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	0.002	0.002
Cobalt	mg/L	0.0001			0.0002	0.0002	0.0001	0.0002
Copper	mg/L	0.0001	1	AO	0.0008	0.0011	0.0006	0.0008
Lead	mg/L	0.00002	0.010	MAC	0.00004	0.00008	0.00006	<0.00002
Molybdenum	mg/L	0.0001			<0.0001	<0.0001	0.0002	<0.0001
Nickel	mg/L	0.0002			0.0003	0.0002	0.0011	0.0003
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

Final Report

REPORT No: 23-005581 - Rev. 1

-								
				Client I.D.	OW 9A	OW 12A	OW 6A	OW 8A
				Sample I.D.	23-005581-1	23-005581-2	23-005581-3	23-005581-4
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00016	<0.00005	0.00019	0.00020
Vanadium	mg/L	0.0001			0.0001	0.0002	<0.0001	0.0001

REPORT No: 23-005581 - Rev. 1

							REPURI NO: 2	3-005581 - Rev. 1
				Client I.D.	OW 22C	OW 23C	OW 5A	OW 5B
				Sample I.D.	23-005581-5	23-005581-6	23-005581-7	23-005581-8
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	256	253	301	288
Bicarbonate (as CaCO3)	mg/L as CaCO3	5			256	253	301	288
pH @25°C	pH units	-	8.5	OG	7.97	7.99	7.99	7.93
Conductivity @25°C	uS/cm	1			643	600	677	737
Chloride	mg/L	0.5	250	AO	15.9	16.0	26.3	56.4
Nitrate (N)	mg/L	0.05	10.0	MAC	8.83	8.08	2.96	2.65
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	37	19	20	15
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	326	318	313	320
Aluminum	mg/L	0.01	0.1	OG	0.04	0.15	0.13	0.07
Barium	mg/L	0.001	1	MAC	0.078	0.029	0.045	0.061
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.008	0.009	0.010	0.010
Calcium	mg/L	0.02			83.1	83.5	95.1	94.9
Iron	mg/L	0.005	0.3	AO	<0.005	0.108	0.073	0.022
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			28.7	26.5	18.3	20.2
Manganese	mg/L	0.001	0.05	AO	<0.001	0.018	0.013	0.002
Phosphorus	mg/L	0.1			<0.1	<0.1	<0.1	<0.1
Potassium	mg/L	0.1			0.8	1.3	3.0	2.0
Silicon	mg/L	0.01			3.28	2.90	2.30	2.40

Final Report REPORT No: 23-005581 - Rev. 1

							REPORT No: 2	3-005581 - Rev. 1
				Client I.D.	OW 22C	OW 23C	OW 5A	OW 5B
				Sample I.D.	23-005581-5	23-005581-6	23-005581-7	23-005581-8
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			7.02	6.21	4.92	5.14
Sodium	mg/L	0.2	200, 20	AO, MAC	3.2	3.2	15.8	26.3
Strontium	mg/L	0.001			0.155	0.107	0.141	0.143
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	0.021	<0.005	0.029
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	0.0001	0.0009	0.0001	0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	<0.000015	0.000015	<0.000015	0.000040
Chromium	mg/L	0.001	0.05	MAC	<0.001	0.001	<0.001	0.001
Cobalt	mg/L	0.0001			0.0001	0.0003	0.0002	0.0002
Copper	mg/L	0.0001	1	AO	0.0003	0.0008	0.0012	0.0029
Lead	mg/L	0.00002	0.010	MAC	<0.00002	0.00074	0.00032	0.00009
Molybdenum	mg/L	0.0001			0.0001	0.0001	0.0001	0.0003
Nickel	mg/L	0.0002			<0.0002	0.0006	0.0002	0.0008
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

Final Report

REPORT No: 23-005581 - Rev. 1

-								
				Client I.D.	OW 22C	OW 23C	OW 5A	OW 5B
				Sample I.D.	23-005581-5	23-005581-6	23-005581-7	23-005581-8
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00039	0.00032	0.00034	0.00041
Vanadium	mg/L	0.0001			0.0001	0.0006	0.0002	<0.0001

REPORT No: 23-005581 - Rev. 1

							ILLI OILI IIO. 2	.3-005561 - Rev. 1
				Client I.D.	OW 7A	OW 7C	OW 4A	OW 4B
				Sample I.D.	23-005581-9	23-005581-10	23-005581-11	23-005581-12
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	262	69	268	328
Bicarbonate (as CaCO3)	mg/L as CaCO3	5			262	68	268	328
pH @25°C	pH units	-	8.5	OG	7.95	8.33	8.07	7.92
Conductivity @25°C	uS/cm	1			590	133	717	783
Chloride	mg/L	0.5	250	AO	15.9	2.7	11.6	44.1
Nitrate (N)	mg/L	0.05	10.0	MAC	1.86	<0.05	22.7	6.36
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	29	<1	11	8
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	294	61.9	320	378
Aluminum	mg/L	0.01	0.1	OG	0.06	0.01	0.07	0.07
Barium	mg/L	0.001	1	MAC	0.069	0.001	0.050	0.067
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.013	0.010	0.010	0.008
Calcium	mg/L	0.02			89.3	4.71	96.4	115
Iron	mg/L	0.005	0.3	AO	<0.005	0.041	<0.005	<0.005
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			17.3	12.2	19.1	21.9
Manganese	mg/L	0.001	0.05	AO	<0.001	0.054	0.001	<0.001
Phosphorus	mg/L	0.1			<0.1	<0.1	<0.1	<0.1
Potassium	mg/L	0.1			1.8	0.9	2.0	0.7
Silicon	mg/L	0.01			2.30	0.04	2.65	2.60

Final Report REPORT No: 23-005581 - Rev. 1

Client I.D. OW 7A OW 7C OW 4A OW 4B 23-005581-12 Sample I.D. 23-005581-9 23-005581-10 23-005581-11 2023-Mar-28 2023-Mar-28 2023-Mar-28 2023-Mar-28 **Date Collected** DWG Parameter Units R.L. Limits Silica 0.07 mg/L 0.02 4.92 5.67 5.56 Sodium mg/L 0.2 200, 20 AO, MAC 6.1 2.0 12.2 18.3 0.001 Strontium mg/L 0.148 0.006 0.170 0.172 Tin mg/L 0.05 < 0.05 < 0.05 <0.05 < 0.05 Titanium 0.005 <0.005 <0.005 <0.005 <0.005 mg/L 0.01 < 0.01 < 0.01 < 0.01 < 0.01 Tungsten mg/L Zinc mg/L 0.005 5 ΑO < 0.005 < 0.005 < 0.005 < 0.005 Zirconium 0.003 < 0.003 < 0.003 < 0.003 < 0.003 mg/L 0.0001 0.006 MAC < 0.0001 <0.0001 < 0.0001 < 0.0001 Antimony mg/L 0.0001 0.01 MAC 0.0001 <0.0001 0.0001 <0.0001 Arsenic mg/L 0.0001 <0.0001 <0.0001 Beryllium mg/L < 0.0001 <0.0001 Cadmium mg/L 0.000015 0.005 MAC < 0.000015 < 0.000015 < 0.000015 < 0.000015 0.001 0.05 MAC < 0.001 <0.001 < 0.001 < 0.001 Chromium mg/L 0.0001 0.0002 0.0002 Cobalt mg/L <0.0001 0.0002 Copper mg/L 0.0001 1 AO 0.0008 0.0003 0.0026 0.0011 Lead 0.00002 0.010 MAC <0.00002 <0.00002 0.00004 <0.00002 mg/L Molybdenum mg/L 0.0001 0.0002 0.0042 0.0003 < 0.0001 Nickel mg/L 0.0002 0.0002 <0.0002 0.0004 0.0002 Selenium 0.001 0.05 MAC < 0.001 <0.001 < 0.001 < 0.001 mg/L Silver 0.0001 < 0.0001 <0.0001 < 0.0001 < 0.0001 mg/L 0.00005 <0.00005 <0.00005 <0.00005 < 0.00005 Thallium mg/L

Final Report

REPORT No: 23-005581 - Rev. 1

				Client I.D.	OW 7A	OW 7C	OW 4A	OW 4B
				Sample I.D.	23-005581-9	23-005581-10	23-005581-11	23-005581-12
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00074	0.00006	0.00047	0.00014
Vanadium	mg/L	0.0001			<0.0001	<0.0001	0.0001	<0.0001

							REPORT NO: 2	3-005581 - Rev. 1
				Client I.D.	OW 19C	OW 21C	OW 10A	OW 20C
				Sample I.D.	23-005581-13	23-005581-14	23-005581-15	23-005581-16
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	352	258	200	234
Bicarbonate (as CaCO3)	mg/L as CaCO3	5			352	258	200	234
pH @25°C	pH units	-	8.5	OG	7.96	7.95	8.01	8.01
Conductivity @25°C	uS/cm	1			692	497	457	500
Chloride	mg/L	0.5	250	AO	14.9	2.0	14.7	3.8
Nitrate (N)	mg/L	0.05	10.0	MAC	<0.05	0.84	1.31	7.92
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	9	10	19	7
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	356	290	233	259
Aluminum	mg/L	0.01	0.1	OG	0.07	0.36	0.07	0.04
Barium	mg/L	0.001	1	MAC	0.177	0.061	0.071	0.074
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.017	0.007	0.012	0.006
Calcium	mg/L	0.02			100	75.8	65.2	69.3
Iron	mg/L	0.005	0.3	AO	0.025	0.322	0.061	<0.005
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			25.8	24.4	17.0	20.9
Manganese	mg/L	0.001	0.05	AO	0.023	0.026	0.024	<0.001
Phosphorus	mg/L	0.1			<0.1	<0.1	<0.1	<0.1
Potassium	mg/L	0.1			6.4	1.0	1.2	0.6
Silicon	mg/L	0.01			3.06	3.08	2.52	2.81

Final Report REPORT No: 23-005581 - Rev. 1

							REPORT No: 2	3-005581 - Rev. 1
				Client I.D.	OW 19C	OW 21C	OW 10A	OW 20C
				Sample I.D.	23-005581-13	23-005581-14	23-005581-15	23-005581-16
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			6.55	6.59	5.39	6.01
Sodium	mg/L	0.2	200, 20	AO, MAC	4.2	2.6	5.0	2.4
Strontium	mg/L	0.001			0.167	0.114	0.130	0.107
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	0.010	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	0.049	0.042	0.005
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	0.0004	0.0008	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	0.0001	0.0003	0.0005	<0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	<0.000015	0.000062	0.000037	<0.000015
Chromium	mg/L	0.001	0.05	MAC	0.002	0.002	<0.001	<0.001
Cobalt	mg/L	0.0001			0.0002	0.0005	0.0004	0.0001
Copper	mg/L	0.0001	1	AO	0.0004	0.0033	0.0022	0.0005
Lead	mg/L	0.00002	0.010	MAC	<0.00002	0.00301	0.00092	<0.00002
Molybdenum	mg/L	0.0001			<0.0001	0.0001	0.0003	0.0001
Nickel	mg/L	0.0002			0.0008	0.0013	0.0008	0.0005
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

				Client I.D.	OW 19C	OW 21C	OW 10A	OW 20C
				Sample I.D.	23-005581-13	23-005581-14	23-005581-15	23-005581-16
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00032	0.00024	0.00052	0.00019
Vanadium	mg/L	0.0001			<0.0001	0.0007	0.0003	0.0001
				Client I.D.	OW 9A	OW 12A	OW 6A	OW 8A
				Sample I.D.	23-005581-1	23-005581-2	23-005581-3	23-005581-4
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Benzene	µg/L	0.5	1	MAC	<0.5	<0.5	<0.5	<0.5
Ethylbenzene	µg/L	0.5	140, 1.6	MAC, AO	<0.5	<0.5	<0.5	<0.5
Toluene	µg/L	0.5	60	MAC	<0.5	<0.5	<0.5	<0.5
Xylene, m,p-	µg/L	1			<1	<1	<1	<1
Xylene, m,p,o-	µg/L	1.1	90, 20	MAC, AO	<1.1	<1.1	<1.1	<1.1
Xylene, o-	µg/L	0.5			<0.5	<0.5	<0.5	<0.5
PHC F1 (C6-C10)	μg/L	25			<25	<25	<25	<25
PHC F2 (>C10-C16)	μg/L	50			<50	<50	<50	<50
PHC F3 (>C16-C34)	μg/L	400			<400	<400	<400	<400
PHC F4 (>C34-C50)	μg/L	400			<400	<400	<400	<400
Oil & Grease (Total)	mg/L	1.0			9.1	9.3	10.5	8.8

REPORT No: 23-005581 - Rev. 1

				Client I.D.	OW 5A	OW 7A	OW 21C	OW 10A
				Sample I.D.	23-005581-7	23-005581-9	23-005581-14	23-005581-15
				Date Collected	2023-Mar-28	2023-Mar-28	2023-Mar-28	2023-Mar-28
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Benzene	μg/L	0.5	1	MAC	<0.5	<0.5	<0.5	<0.5
Ethylbenzene	μg/L	0.5	140, 1.6	MAC, AO	<0.5	<0.5	<0.5	<0.5
Toluene	μg/L	0.5	60	MAC	<0.5	<0.5	<0.5	<0.5
Xylene, m,p-	μg/L	1			<1	<1	<1	<1
Xylene, m,p,o-	μg/L	1.1	90, 20	MAC, AO	<1.1	<1.1	<1.1	<1.1
Xylene, o-	μg/L	0.5			<0.5	<0.5	<0.5	<0.5
PHC F1 (C6-C10)	μg/L	25			<25	<25	<25	<25
PHC F2 (>C10-C16)	μg/L	50			<50	<50	<50	<50
PHC F3 (>C16-C34)	μg/L	400			<400	<400	<400	<400
PHC F4 (>C34-C50)	μg/L	400			<400	<400	<400	<400
Oil & Grease (Total)	mg/L	1.0			12.1	9.8	8.3	5.2

REPORT No: 23-005581 - Rev. 1

				Client I.D.	OW 20C
Parameter	Units	R.L.	Limits	Sample I.D. Date Collected DWG	23-005581-16 2023-Mar-28
Benzene	μg/L	0.5	1	MAC	<0.5
Ethylbenzene	μg/L	0.5	140, 1.6	MAC, AO	<0.5
Toluene	μg/L	0.5	60	MAC	<0.5
Xylene, m,p-	μg/L	1			<1
Xylene, m,p,o-	μg/L	1.1	90, 20	MAC, AO	<1.1
Xylene, o-	μg/L	0.5			<0.5
PHC F1 (C6-C10)	μg/L	25			<25
PHC F2 (>C10-C16)	μg/L	50			<50
PHC F3 (>C16-C34)	μg/L	400			<400
PHC F4 (>C34-C50)	μg/L	400			<400
Oil & Grease (Total)	mg/L	1.0			8.7

Revised report to update sample ID's as per client request

DWG - Drinking Water Guidelines

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective

OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

Aesthetic Objectives		
OW 7C	Found Value	Limit
Manganese	0.054	0.05
OW 21C	Found Value	Limit
Iron	0.322	0.3
Maximum Acceptable Concentration		
OW 9A	Found Value	Limit
Nitrate (N)	17.3	10.0
OW 8A	Found Value	Limit
Nitrate (N)	14.8	10.0
OW 5B	Found Value	Limit
Sodium	26.3	20
OW 4A	Found Value	Limit
Nitrate (N)	22.7	10.0
Operational Guidelines		
OW 9A	Found Value	Limit
Hardness (as CaCO3)	413	100
OW 12A	Found Value	Limit
Hardness (as CaCO3)	190	100
OW 6A	Found Value	Limit
Hardness (as CaCO3)	249	100
OW 8A	Found Value	Limit
Hardness (as CaCO3)	380	100
OW 22C	Found Value	Limit
Hardness (as CaCO3)	326	100
OW 23C	Found Value	Limit
Hardness (as CaCO3)	318	100
Aluminum	0.15	0.1
OW 5A	Found Value	Limit
Hardness (as CaCO3)	313	100
Aluminum	0.13	0.1
OW 5B	Found Value	Limit
Hardness (as CaCO3)	320	100
OW 7A	Found Value	Limit
Hardness (as CaCO3)	294	100
OW 4A	Found Value	Limit
Hardness (as CaCO3)	320	100
OW 4B	Found Value	Limit

Hardness (as CaCO3)	378	100
OW 19C	Found Value	Limit
Hardness (as CaCO3)	356	100
OW 21C	Found Value	Limit
Hardness (as CaCO3)	290	100
Aluminum	0.36	0.1
OW 10A	Found Value	Limit
Hardness (as CaCO3)	233	100
OW 20C	Found Value	Limit
Hardness (as CaCO3)	259	100

CERTIFICATE OF ANALYSIS



Final Report

C.O.C.: - REPORT No: 23-029474 - Rev. 0

Report To:

Tatham Engineering
115 Sandford Fleming Drive

Suite 200

Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

DATE RECEIVED:

DATE REPORTED:

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8

2023-Oct-20 CUSTOMER PROJECT: 123016

2023-Oct-31 P.O. NUMBER:

SAMPLE MATRIX: Ground Water

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	19	OTTAWA	PCURIEL	2023-Oct-25	A-IC-01	SM 4110B
Cond/pH/Alk Auto (Liquid)	19	OTTAWA	SBOUDREAU	2023-Oct-25	COND-02/PH-02/A	SM 2510B/4500H/
					LK-02	2320B
ICP/MS (Liquid)	19	OTTAWA	AOZKAYMAK	2023-Oct-26	D-ICPMS-01	EPA 200.8
ICP/OES (Liquid)	19	OTTAWA	APRUDYVUS	2023-Oct-25	D-ICP-01	SM 3120B
TP & TKN (Liquid)	19	KINGSTON	KDIBBITS	2023-Oct-30	TPTKN-001	MECP E3516.2

R.L. = Reporting Limit

NC = Not Calculated

Test methods may be modified from specified reference method unless indicated by an $\,^\star$

REPORT No: 23-029474 - Rev. 0

							REPORT NO: 2	3-029474 - Rev. 0
				Client I.D.	OW4A	OW4B	OW5A	OW5B
				Sample I.D.	23-029474-1	23-029474-2	23-029474-3	23-029474-4
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-18
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	322	329	290	292
Bicarbonate (as CaCO3)	mg/L	5			322	329	290	292
pH @25°C	pH units	-	8.5	OG	7.88	7.58	7.52	7.50
Conductivity @25°C	uS/cm	1			760	8	765	770
Chloride	mg/L	0.5	250	AO	22.0	43.4	61.2	60.7
Nitrate (N)	mg/L	0.05	10.0	MAC	11.5	10.3	3.67	3.65
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	0.10	<0.05	<0.05
Sulphate	mg/L	1	500	AO	12	10	14	15
Phosphorus (Total)	mg/L	0.01			2.20	0.15	0.51	2.06
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	399	421	346	353
Aluminum	mg/L	0.01	0.1	OG	0.05	0.03	0.04	0.03
Barium	mg/L	0.001	1	MAC	0.051	0.069	0.045	0.044
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.007	0.010	0.011	0.010
Calcium	mg/L	0.02			122	127	99.4	102
Iron	mg/L	0.005	0.3	AO	<0.005	0.007	0.008	0.131
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			22.8	25.1	23.8	23.9
Manganese	mg/L	0.001	0.05	AO	0.008	0.002	0.002	0.029
Potassium	mg/L	0.1			2.1	0.9	2.8	2.4
Silicon	mg/L	0.01			4.32	3.87	3.76	3.74

Final Report REPORT No: 23-029474 - Rev. 0

							REPORT NO. 2	3-029474 - Rev. 0
				Client I.D.	OW4A	OW4B	OW5A	OW5B
				Sample I.D.	23-029474-1	23-029474-2	23-029474-3	23-029474-4
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-18
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			9.23	8.28	8.04	8.00
Sodium	mg/L	0.2	200, 20, 20	AO, WL, MAC	10.8	20.8	33.6	32.6
Strontium	mg/L	0.001			0.195	0.181	0.149	0.150
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	<0.005	<0.005	0.026
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	0.0004	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	0.0002 (11)	<0.0001	<0.0001	0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	<0.000015	<0.000015	<0.000015	0.000027
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Cobalt	mg/L	0.0001			0.0002	0.0002	0.0002	0.0002
Copper	mg/L	0.0001	1	AO	0.0006	0.0010	0.0015	0.0017
Lead	mg/L	0.00002	0.010	MAC	<0.00002	0.00002	0.00002	0.00004
Molybdenum	mg/L	0.0001			0.0003	<0.0001	0.0002	0.0003
Nickel	mg/L	0.0002			0.0013	0.0011	0.0009	0.0004
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

Final Report

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW4A	OW4B	OW5A	OW5B		
				Sample I.D.	23-029474-1	23-029474-2	23-029474-3	23-029474-4		
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-18		
Parameter	Units	R.L.	Limits	DWG	-	-	-	-		
Uranium	mg/L	0.00005	0.02	MAC	0.00022	0.00014	0.00046	0.00050		
Vanadium	mg/L	0.0001			0.0002	<0.0001	<0.0001	<0.0001		

REPORT No: 23-029474 - Rev. 0

,							112. 31(110.2	.3-0294/4 - Rev. 0
				Client I.D.	OW6A	OW7A	OW7C	OW8A
				Sample I.D.	23-029474-5	23-029474-6	23-029474-7	23-029474-8
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-16
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	180	287	86	312
Bicarbonate (as CaCO3)	mg/L	5			180	287	86	312
pH @25°C	pH units	-	8.5	OG	7.28	7.63	7.54	7.63
Conductivity @25°C	uS/cm	1			413	596	140	963
Chloride	mg/L	0.5	250	AO	15.9	12.8	3.1	60.5
Nitrate (N)	mg/L	0.05	10.0	MAC	0.86	1.32	<0.05	26.5
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	20	20	<1	11
Phosphorus (Total)	mg/L	0.01			0.28	2.12	0.01	5.42
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	215	333	73.9	497
Aluminum	mg/L	0.01	0.1	OG	0.02	0.05	0.01	0.04
Barium	mg/L	0.001	1	MAC	0.053	0.069	0.002	0.133
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.020	0.013	0.015	0.008
Calcium	mg/L	0.02			60.5	102	4.74	129
Iron	mg/L	0.005	0.3	AO	0.012	0.072	0.022	0.011
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			15.5	19.0	15.1	42.5
Manganese	mg/L	0.001	0.05	AO	0.003	0.008	0.029	<0.001
Potassium	mg/L	0.1			2.6	1.7	0.9	1.4
Silicon	mg/L	0.01			2.62	3.52	0.07	6.09

Final Report REPORT No: 23-029474 - Rev. 0

							1121 0111 110. 2	3-025474 - Rev. U
				Client I.D.	OW6A	OW7A	OW7C	OW8A
				Sample I.D.	23-029474-5	23-029474-6	23-029474-7	23-029474-8
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-16
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			5.61	7.54	0.14	13.0
Sodium	mg/L	0.2	200, 20, 20	AO, WL, MAC	4.8	6.2	2.1	12.3
Strontium	mg/L	0.001			0.138	0.145	0.005	0.225
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	<0.005	<0.005	<0.005
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	<0.000015	<0.000015	<0.000015	<0.000015
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Cobalt	mg/L	0.0001			<0.0001	0.0002	<0.0001	0.0002
Copper	mg/L	0.0001	1	AO	0.0012	0.0015	0.0003	0.0010
Lead	mg/L	0.00002	0.010	MAC	0.00002	0.00014	0.00002	<0.00002
Molybdenum	mg/L	0.0001			0.0003	<0.0001	0.0045	<0.0001
Nickel	mg/L	0.0002			0.0006	0.0010	0.0002	<0.0002
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

Michelle Dubien

Final Report

REPORT No: 23-029474 - Rev. 0

-										
				Client I.D.	OW6A	OW7A	OW7C	OW8A		
				Sample I.D.	23-029474-5	23-029474-6	23-029474-7	23-029474-8		
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-16		
Parameter	Units	R.L.	Limits	DWG	-	-	-	-		
Uranium	mg/L	0.00005	0.02	MAC	0.00017	0.00018	<0.00005	0.00023		
Vanadium	mg/L	0.0001			<0.0001	0.0001	<0.0001	0.0001		

REPORT No: 23-029474 - Rev. 0

							ILLI OILLI IIO. 2	.3-025474 - Rev. 0
				Client I.D.	OW9A	OW10A	OW12A	OW13C
				Sample I.D.	23-029474-9	23-029474-10	23-029474-11	23-029474-12
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-17
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	393	209	154	299
Bicarbonate (as CaCO3)	mg/L	5			393	209	154	299
pH @25°C	pH units	-	8.5	OG	7.75	7.41	7.24	7.74
Conductivity @25°C	uS/cm	1			821	442	290	600
Chloride	mg/L	0.5	250	AO	9.4	10.7	1.4	11.3
Nitrate (N)	mg/L	0.05	10.0	MAC	8.79	1.13	1.18	1.76
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	9	16	3	7
Phosphorus (Total)	mg/L	0.01			0.82	2.39	7.59	0.03
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	476	237	154	329
Aluminum	mg/L	0.01	0.1	OG	0.05	0.02	0.02	0.03
Barium	mg/L	0.001	1	MAC	0.083	0.054	0.004	0.039
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.010	0.015	0.008	0.009
Calcium	mg/L	0.02			151	66.0	53.8	94.6
Iron	mg/L	0.005	0.3	AO	0.013	0.013	0.016	0.006
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			24.0	17.6	4.79	22.5
Manganese	mg/L	0.001	0.05	AO	0.012	0.028	<0.001	0.001
Potassium	mg/L	0.1			0.9	1.2	1.3	1.3
Silicon	mg/L	0.01			5.59	3.46	2.59	3.72

REPORT No: 23-029474 - Rev. 0

							TKET OILT 140. 2	3-029474 - Rev. U
				Client I.D.	OW9A	OW10A	OW12A	OW13C
				Sample I.D.	23-029474-9	23-029474-10	23-029474-11	23-029474-12
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-17
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			12.0	7.41	5.53	7.95
Sodium	mg/L	0.2	200, 20, 20	AO, WL, MAC	3.0	4.3	0.7	7.1
Strontium	mg/L	0.001			0.212	0.122	0.118	0.121
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	<0.005	0.031	<0.005	0.019
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	<0.0001	0.0003	<0.0001	0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	<0.000015	<0.000015	<0.000015	<0.000015
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Cobalt	mg/L	0.0001			0.0002	0.0003	0.0001	0.0001
Copper	mg/L	0.0001	1	AO	0.0012	0.0008	0.0021	0.0008
Lead	mg/L	0.00002	0.010	MAC	0.00003	0.00002	0.00003	0.00003
Molybdenum	mg/L	0.0001			<0.0001	0.0003	0.0002	0.0002
Nickel	mg/L	0.0002			<0.0002	0.0004	0.0006	0.0008
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

Michelle Dubien

Final Report

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW9A	OW10A	OW12A	OW13C
				Sample I.D.	23-029474-9	23-029474-10	23-029474-11	23-029474-12
				Date Collected	2023-Oct-18	2023-Oct-18	2023-Oct-18	2023-Oct-17
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00014	0.00042	<0.00005	0.00017
Vanadium	mg/L	0.0001			0.0001	<0.0001	0.0002	0.0001

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW14C	OW18A	OW18C	OW20C
				Sample I.D.	23-029474-13	23-029474-14	23-029474-15	23-029474-16
				Date Collected	2023-Oct-17	2023-Oct-17	2023-Oct-17	2023-Oct-17
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	465	189	262	235
Bicarbonate (as CaCO3)	mg/L	5			465	189	262	235
pH @25°C	pH units	-	8.5	OG	7.67	7.41	7.56	7.75
Conductivity @25°C	uS/cm	1			871	381	518	514
Chloride	mg/L	0.5	250	AO	2.9	5.6	6.8	4.5
Nitrate (N)	mg/L	0.05	10.0	MAC	4.53	1.18	1.29	8.86
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	7	8	8	8
Phosphorus (Total)	mg/L	0.01			0.63	2.87	1.09	0.66
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	509	211	267	291
Aluminum	mg/L	0.01	0.1	OG	0.05	0.03	0.02	0.02
Barium	mg/L	0.001	1	MAC	0.111	0.038	0.033	0.074
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.011	0.008	0.008	0.007
Calcium	mg/L	0.02			143	63.1	77.5	75.2
Iron	mg/L	0.005	0.3	AO	0.036	0.028	0.006	0.005
Lithium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			36.8	13.0	17.9	25.0
Manganese	mg/L	0.001	0.05	AO	<0.001	0.002	<0.001	<0.001
Potassium	mg/L	0.1			0.9	0.6	0.8	0.5
Silicon	mg/L	0.01			5.60	2.86	3.34	4.40

Michelle Dubien

REPORT No: 23-029474 - Rev. 0

							REPORT No: 2	3-029474 - Rev. 0
				Client I.D.	OW14C	OW18A	OW18C	OW20C
				Sample I.D.	23-029474-13	23-029474-14	23-029474-15	23-029474-16
				Date Collected	2023-Oct-17	2023-Oct-17	2023-Oct-17	2023-Oct-17
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Silica	mg/L	0.02			12.0	6.13	7.14	9.42
Sodium	mg/L	0.2	200, 20, 20	AO, WL, MAC	2.0	2.4	3.2	2.3
Strontium	mg/L	0.001			0.206	0.085	0.100	0.116
Tin	mg/L	0.05			<0.05	<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	0.132	<0.005	<0.005	0.006
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	<0.0001	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	0.0001	<0.0001	0.0001	<0.0001
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	0.000064	<0.000015	<0.000015	<0.000015
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Cobalt	mg/L	0.0001			0.0002	0.0001	0.0001	0.0001
Copper	mg/L	0.0001	1	AO	0.0010	0.0014	0.0017	0.0017
Lead	mg/L	0.00002	0.010	MAC	0.00004	0.00004	0.00003	0.00003
Molybdenum	mg/L	0.0001			<0.0001	0.0001	0.0002	0.0002
Nickel	mg/L	0.0002			0.0006	0.0007	0.0008	0.0007
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005	<0.00005

Michelle Dubien

Final Report

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW14C	OW18A	OW18C	OW20C
				Sample I.D. Date Collected	23-029474-13 2023-Oct-17	23-029474-14 2023-Oct-17	23-029474-15 2023-Oct-17	23-029474-16 2023-Oct-17
Parameter	Units	R.L.	Limits	DWG	-	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00020	0.00012	0.00012	0.00026
Vanadium	mg/L	0.0001			<0.0001	<0.0001	<0.0001	0.0001

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW21C	OW22C	OW23C
				Offent I.D.	OWZTO	OW220	OW230
				Sample I.D. Date Collected	23-029474-17 2023-Oct-17	23-029474-18 2023-Oct-17	23-029474-19 2023-Oct-18
Parameter	Units	R.L.	Limits	DWG	-	-	-
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	264	270	262
Bicarbonate (as CaCO3)	mg/L	5			264	270	262
pH @25°C	pH units	-	8.5	OG	7.73	7.60	7.64
Conductivity @25°C	uS/cm	1			486	660	613
Chloride	mg/L	0.5	250	AO	1.5	15.4	15.4
Nitrate (N)	mg/L	0.05	10.0	MAC	0.51	9.22	8.25
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	10	36	19
Phosphorus (Total)	mg/L	0.01			1.76	0.08	1.46
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100	OG	287	369	341
Aluminum	mg/L	0.01	0.1	OG	0.03	0.03	0.04
Barium	mg/L	0.001	1	MAC	0.060	0.082	0.027
Bismuth	mg/L	0.02			<0.02	<0.02	<0.02
Boron	mg/L	0.005	5	MAC	0.012	0.012	0.007
Calcium	mg/L	0.02			74.5	91.7	86.6
Iron	mg/L	0.005	0.3	AO	0.016	0.010	0.010
Lithium	mg/L	0.005			<0.005	<0.005	<0.005
Magnesium	mg/L	0.02			24.4	34.0	30.4
Manganese	mg/L	0.001	0.05	AO	<0.001	<0.001	0.001
Potassium	mg/L	0.1			0.5	0.9	1.3
Silicon	mg/L	0.01			4.42	5.21	4.26

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW21C	OW22C	OW23C
				Sample I.D. Date Collected	23-029474-17 2023-Oct-17	23-029474-18 2023-Oct-17	23-029474-19 2023-Oct-18
Parameter	Units	R.L.	Limits	DWG	-	-	-
Silica	mg/L	0.02			9.45	11.2	9.12
Sodium	mg/L	0.2	200, 20, 20	AO, WL, MAC	1.9	3.5	3.3
Strontium	mg/L	0.001			0.117	0.165	0.109
Tin	mg/L	0.05			<0.05	<0.05	<0.05
Titanium	mg/L	0.005			<0.005	<0.005	<0.005
Tungsten	mg/L	0.01			<0.01	<0.01	<0.01
Zinc	mg/L	0.005	5	AO	0.007	0.005	0.010
Zirconium	mg/L	0.003			<0.003	<0.003	<0.003
Antimony	mg/L	0.0001	0.006	MAC	<0.0001	<0.0001	<0.0001
Arsenic	mg/L	0.0001	0.01	MAC	<0.0001	0.0001	0.0005
Beryllium	mg/L	0.0001			<0.0001	<0.0001	<0.0001
Cadmium	mg/L	0.000015	0.005	MAC	<0.000015	<0.000015	<0.000015
Chromium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001
Cobalt	mg/L	0.0001			0.0001	0.0001	0.0001
Copper	mg/L	0.0001	1	AO	0.0010	0.0011	0.0004
Lead	mg/L	0.00002	0.010	MAC	0.00002	0.00002	0.00004
Molybdenum	mg/L	0.0001			0.0001	0.0002	0.0001
Nickel	mg/L	0.0002			0.0007	0.0009	0.0009
Selenium	mg/L	0.001	0.05	MAC	<0.001	<0.001	<0.001
Silver	mg/L	0.0001			<0.0001	<0.0001	<0.0001
Thallium	mg/L	0.00005			<0.00005	<0.00005	<0.00005

Final Report

REPORT No: 23-029474 - Rev. 0

				Client I.D.	OW21C	OW22C	OW23C
				Sample I.D.	23-029474-17	23-029474-18	23-029474-19
				Date Collected	2023-Oct-17	2023-Oct-17	2023-Oct-18
Parameter	Units	R.L.	Limits	DWG	-	-	-
Uranium	mg/L	0.00005	0.02	MAC	0.00020	0.00042	0.00031
Vanadium	mg/L	0.0001			<0.0001	0.0001	0.0001

Comments:

11. Filtered from GWC.

DWG - Drinking Water Guidelines

ODWS - Ontario Drinking Water Standards AO - Aesthetic Objectives IMAC - Interim Maximum Acceptable Concentration MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

Maximum Acceptable Concentration		
OW4A	Found Value	Limit
Nitrate (N)	11.5	10.0
OW4B	Found Value	Limit
Nitrate (N)	10.3	10.0
Sodium	20.8	20
OW5A	Found Value	Limit
Sodium	33.6	20
OW5B	Found Value	Limit
Sodium	32.6	20
A8WO	Found Value	Limit
Nitrate (N)	26.5	10.0
Operational Guidelines		
OW4A	Found Value	Limit
Hardness (as CaCO3)	399	100
OW4B	Found Value	Limit
Hardness (as CaCO3)	421	100
OW5A	Found Value	Limit
Hardness (as CaCO3)	346	100
OW5B	Found Value	Limit
Hardness (as CaCO3)	353	100
OW6A	Found Value	Limit
Hardness (as CaCO3)	215	100
OW7A	Found Value	Limit
Hardness (as CaCO3)	333	100
A8WO	Found Value	Limit
Hardness (as CaCO3)	497	100
OW9A	Found Value	Limit
Hardness (as CaCO3)	476	100
OW10A	Found Value	Limit
Hardness (as CaCO3)	237	100
OW12A	Found Value	Limit
Hardness (as CaCO3)	154	100
OW13C	Found Value	Limit
Hardness (as CaCO3)	329	100
OW14C	Found Value	Limit
Hardness (as CaCO3)	509	100
OW18A	Found Value	Limit

Hardness (as CaCO3)	211	100
OW18C	Found Value	Limit
Hardness (as CaCO3)	267	100
OW20C	Found Value	Limit
Hardness (as CaCO3)	291	100
OW21C	Found Value	Limit
Hardness (as CaCO3)	287	100
OW22C	Found Value	Limit
Hardness (as CaCO3)	369	100
OW23C	Found Value	Limit
Hardness (as CaCO3)	341	100
Warning Level - Sodium Restricted Diets		
OW4B	Found Value	Limit
Sodium	20.8	20
OW5A	Found Value	Limit
Sodium	33.6	20
OW5B	Found Value	Limit
Sodium	32.6	20



CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: - REPORT No: 23-011900 - Rev. 0

Report To:

Tatham Engineering 115 Sandford Fleming Drive Suite 200

Collingwood, ON L9Y 5A6

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8

Attention: Jordon Miller

DATE RECEIVED: 2023-May-26

DATE REPORTED: 2023-Jun-12

SAMPLE MATRIX: Surface Water

CUSTOMER PROJECT: 123016

P.O. NUMBER:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	2	OTTAWA	PCURIEL	2023-May-30	A-IC-01	SM 4110B
Cond/pH/Alk Auto (Liquid)	2	OTTAWA	SBOUDREAU	2023-May-30	COND-02/PH-02/A	SM 2510B/4500H/
					LK-02	2320B
ICP/MS Total (Liquid)	2	OTTAWA	TPRICE	2023-May-31	D-ICPMS-01	EPA 6020
ICP/OES Total (Liquid)	2	OTTAWA	NHOGAN	2023-May-31	D-ICP-01	SM 3120B

R.L. = Reporting Limit

NC = Not Calculated

Test methods may be modified from specified reference method unless indicated by an *

REPORT No: 23-011900 - Rev. 0

				Client I.D.	South Pond 23-011900-9	North Pond 23-011900-10
Parameter	Units	R.L.	Limits	Date Collected	2023-May-24 -	2023-May-24 -
Alkalinity(CaCO3) to pH4.5	mg/L	5			218	250
Bicarbonate (as CaCO3)	mg/L	5			218	250
pH @25°C	pH units	-	8.5	PWQO	8.11	8.12
Conductivity @25°C	uS/cm	1			395	482
Chloride	mg/L	0.5			1.5	7.0
Nitrate (N)	mg/L	0.05			0.15	0.14
Nitrite (N)	mg/L	0.05			<0.05	<0.05
Sulphate	mg/L	1			2	10
Hardness (as CaCO3)	mg/L	-			232	256
Aluminum (Total)	mg/L	0.01			0.05	0.07
Barium (Total)	mg/L	0.001			0.019	0.037
Bismuth (Total)	mg/L	0.02			<0.02	<0.02
Boron (Total)	µg/L	5	200	INTERIM	11	9
Calcium (Total)	mg/L	0.02			81.1	83.0
Iron (Total)	µg/L	5	300	PWQO	95	94
Lithium (Total)	mg/L	0.005			<0.005	<0.005
Magnesium (Total)	mg/L	0.02			7.21	11.8
Manganese (Total)	mg/L	0.001			0.038	0.029
Phosphorus (Total)	mg/L	0.1			<0.1	<0.1
Potassium (Total)	mg/L	0.1			2.5	2.2
Silicon (Total)	mg/L	0.01			1.09	1.64

Final Report

REPORT No: 23-011900 - Rev. 0

				Client I.D.	South Pond	North Pond
				Sample I.D.	23-011900-9	23-011900-10
Parameter	Units	R.L.	Limits	Date Collected	2023-May-24	2023-May-24
Silica (Total)	mg/L	0.02	Liiiits		2.33	3.51
Sodium (Total)	mg/L	0.2			1.6	2.5
Strontium (Total)	mg/L	0.001			0.119	0.111
Tin (Total)	mg/L	0.05			<0.05	<0.05
Titanium (Total)	mg/L	0.005			<0.005	<0.005
Tungsten (Total)	μg/L	10	30	INTERIM	<10	<10
Zinc (Total)	μg/L	5	20, 30	INTERIM, PWQO	<5	<5
Zirconium (Total)	μg/L	3	4	INTERIM	<3	<3
Antimony (Total)	μg/L	0.1	20	INTERIM	0.1	<0.1
Arsenic (Total)	μg/L	0.1	5, 5	INTERIM, PWQO	0.6	0.6
Beryllium (Total)	μg/L	0.1	11	PWQO	<0.1	<0.1
Cadmium (Total)	μg/L	0.015	0.1, 0.2	INTERIM, PWQO	0.019	0.022
Chromium (Total)	mg/L	0.001			<0.001	<0.001
Cobalt (Total)	μg/L	0.1	0.9	INTERIM	0.2	0.2
Copper (Total)	μg/L	0.1	5	INTERIM	0.7	0.8
Lead (Total)	μg/L	0.02	1, 5	INTERIM, PWQO	0.06	0.02
Molybdenum (Total)	μg/L	0.1	40	INTERIM	0.2	0.2
Nickel (Total)	μg/L	0.2	25	PWQO	0.5	0.4
Selenium (Total)	µg/L	1	100	PWQO	<1	<1
Silver (Total)	μg/L	0.1	0.1	PWQO	<0.1	<0.1
Thallium (Total)	μg/L	0.05	0.3, 0.3	INTERIM, PWQO	<0.05	<0.05

Final Report

REPORT No: 23-011900 - Rev. 0

				Client I.D.	South Pond	North Pond
				Sample I.D.	23-011900-9	23-011900-10
				Date Collected	2023-May-24	2023-May-24
Parameter	Units	R.L.	Limits		-	-
Uranium (Total)	μg/L	0.05	5	INTERIM	0.39	0.63
Vanadium (Total)	μg/L	0.100	6	INTERIM	<0.100	<0.100

: PWQO Limits INTERIM: Interim PWQO PWQO: PWQO



CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: - REPORT No: 23-029907 - Rev. 1

Report To:

Tatham Engineering 115 Sandford Fleming Drive Suite 200

Collingwood, ON L9Y 5A6

CADUCEON Environmental Laboratories

CUSTOMER PROJECT: 123016

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8

P.O. NUMBER:

Attention: Oliver Lestyan

DATE REPORTED:

DATE RECEIVED: 2023-Oct-25

2024-Mar-13

SAMPLE MATRIX: Surface Water

ENVIRONMENTAL LABORATOR E

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	2	OTTAWA	VKASYAN	2023-Oct-27	A-IC-01	SM 4110B
Cond/pH/Alk Auto (Liquid)	2	OTTAWA	SBOUDREAU	2023-Oct-27	COND-02/PH-02/A	SM 2510B/4500H/
					LK-02	2320B
ICP/MS Total (Liquid)	2	OTTAWA	TPRICE	2023-Oct-27	D-ICPMS-01	EPA 6020
ICP/OES Total (Liquid)	2	OTTAWA	NHOGAN	2023-Oct-27	D-ICP-01	SM 3120B
TP & TKN (Liquid)	2	KINGSTON	KDIBBITS	2023-Oct-30	TPTKN-001	MECP E3516.2

R.L. = Reporting Limit

NC = Not Calculated

Test methods may be modified from specified reference method unless indicated by an $\,^\star$

				Client I.D.	North Pond	South Pond
				Sample I.D. Date Collected	23-029907-1 2023-Oct-19	23-029907-2 2023-Oct-19
Parameter	Units	R.L.	Limits			
Alkalinity(CaCO3) to pH4.5	mg/L	5			204	171
Bicarbonate (as CaCO3)	mg/L	5			204	171
Conductivity @25°C	uS/cm	1			383	317
pH @25°C	pH units	-	8.5	PWQO	7.87	7.97
Chloride	mg/L	0.5			7.0	1.5
Nitrate (N)	mg/L	0.05			0.12	0.07
Nitrite (N)	mg/L	0.05			<0.05	<0.05
Sulphate	mg/L	1			3	<1
Phosphorus (Total)	μg/L	10	10	INTERIM	40	100
Hardness (as CaCO3)	mg/L as CaCO3	-			169	146
Aluminum (Total)	μg/L	10			50	40
Barium (Total)	μg/L	1			28	7
Bismuth (Total)	μg/L	20			<20	<20
Boron (Total)	μg/L	5	200	INTERIM	9	6
Calcium (Total)	μg/L	20			49300	48500
Iron (Total)	μg/L	5	300	PWQO	564	124
Lithium (Total)	μg/L	5			<5	<5
Magnesium (Total)	μg/L	20			11100	6100
Manganese (Total)	μg/L	1			20	39
Phosphorus (Total)	μg/L	100			<100	<100
Potassium (Total)	μg/L	100			4100	5100

				Client I.D.	North Pond	South Pond
				Sample I.D. Date Collected	23-029907-1 2023-Oct-19	23-029907-2 2023-Oct-19
Parameter	Units	R.L.	Limits		-	-
Silicon (Total)	μg/L	10			2610	250
Silica (Total)	μg/L	20			5590	530
Sodium (Total)	μg/L	200			2200	1100
Strontium (Total)	μg/L	1			93	67
Tin (Total)	μg/L	50			<50	<50
Tungsten (Total)	μg/L	10	30	INTERIM	<10	<10
Zinc (Total)	μg/L	5	20, 30	INTERIM, PWQO	14	16
Zirconium (Total)	μg/L	3	4	INTERIM	<3	<3
Antimony (Total)	μg/L	0.1	20	INTERIM	0.3	0.4
Arsenic (Total)	μg/L	0.1	5, 5	INTERIM, PWQO	0.8	0.4
Beryllium (Total)	μg/L	0.1	11	PWQO	<0.1	<0.1
Cadmium (Total)	μg/L	0.015	0.1, 0.2	INTERIM, PWQO	<0.015	0.024
Chromium (Total)	μg/L	1			<1	<1
Cobalt (Total)	μg/L	0.1	0.9	INTERIM	0.2	0.2
Copper (Total)	μg/L	0.1	5	INTERIM	0.3	0.6
Lead (Total)	μg/L	0.02	1, 5	INTERIM, PWQO	0.06	0.04
Molybdenum (Total)	μg/L	0.1	40	INTERIM	0.2	0.2
Nickel (Total)	μg/L	0.2	25	PWQO	0.9	0.7
Selenium (Total)	μg/L	1	100	PWQO	<1	<1
Silver (Total)	μg/L	0.1	0.1	PWQO	<0.1	<0.1
Thallium (Total)	μg/L	0.05	0.3, 0.3	INTERIM, PWQO	<0.05	<0.05

Final Report

REPORT No: 23-029907 - Rev. 1

				Client I.D.	North Pond	South Pond
				Sample I.D.	23-029907-1	23-029907-2
				Date Collected	2023-Oct-19	2023-Oct-19
Parameter	Units	R.L.	Limits		-	-
Uranium (Total)	μg/L	0.05	5	INTERIM	0.29	0.20
Vanadium (Total)	μg/L	0.1	6	INTERIM	<0.1	0.1

Revised report to include guidelines as per client request

: PWQO Limits

INTERIM: Interim PWQO PWQO: PWQO

Summary of Exceedances			
Interim PWQO			
North Pond	Four	nd Value	Limit
Phosphorus (Total)		40	10
South Pond	Four	nd Value	Limit
Phosphorus (Total)		100	10
PWQO	·		
North Pond	Four	nd Value	Limit
Iron (Total)		564	300

Appendix F: Domestic Water Monitoring Program Results

tathameng.com



File 123016

February 9, 2024

Dan and Jennifer Robertson

1 Ashlea Lane,
Melancthon Township, Ontario, L9V 3M9
Robertsond24@gmail.com jenharkness@hotmail.com

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mr. and Mrs. Robertson:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to initiate a domestic water well monitoring program as part of the due diligence investigation process associated with the on-going domestic water well monitoring program for the Shelburne Quarry.

In January 2023, Tatham took over the monitoring of the level datalogger in your drilled well, as a part of the monitoring program at the Strada Quarry. A water level datalogger is an instrument used to automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

Manual groundwater levels were measured at depths of 7.8 m below existing grade on May 24, 2023. A hydrograph illustrating the continuous groundwater levels in your well over the course of a year of monitoring is provided for reference. It should be noted this graph only has data from until May of 2023. When the well was visited on October 17, 2023, the logger was missing.

On October 17, 2023, a water sample was taken from your outside faucet, as this typically bypasses any filtration that you may have. Results from this sample have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 279 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.

The operational guideline for hardness is set between 80 to 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water too





Dan and Jennifer Robertson

2

soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO₃) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,


Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo. Group Lead - Hydrogeology

JRM/AK:ha

l:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\2023 Letter\DW2\L - 1 Ashlea Lane - DW Monitoring Program Letter.docx







COC #: DWTE231020

Report To:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

DATE SUBMITTED: 20-Oct-23 DATE REPORTED: 27-Oct-23

SAMPLE MATRIX: **Drinking Water**

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

CUSTOMER PROJECT: 123016 P.O. NUMBER: WATERWORKS NO:

	Client ID:		DW2
	Sample ID:		23-029437-2
	Date Collected:		17-Oct-23
Parameter	Units	R.L.	
Alkalinity(CaCO3) to pH4.5	mg/L	5	283
Bicarbonate (as CaCO3)	mg/L	5	283
pH @25°C	pH units		8.07
Conductivity @25°C	uS/cm	1	583
Chloride	mg/L	0.5	10.4
Nitrate (N)	mg/L	0.05	3.35
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	12
Phosphorus (Total)	mg/L	0.01	<0.01
Total Kjeldahl Nitrogen	mg/L	0.1	<0.1
Hardness (as CaCO3)	mg/L as CaCO3	0.02	279
Aluminum	mg/L	0.01	0.05
Barium	mg/L	0.001	0.032
Bismuth	mg/L	0.02	<0.02
Boron	mg/L	0.005	0.01
Calcium	mg/L	0.02	79.3
Iron	mg/L	0.005	< 0.005
Lithium	mg/L	0.005	< 0.005
Magnesium	mg/L	0.02	19.7
Manganese	mg/L	0.001	<0.001
Nickel	mg/L	0.01	<0.01
Potassium	mg/L	0.1	1
Silicon	mg/L	0.01	3.64
Silica	mg/L	2	8
Sodium	mg/L	0.2	4
Strontium	mg/L	0.001	0.111
Tin	mg/L	0.05	<0.05
Titanium	mg/L	0.005	< 0.005
Tungsten	mg/L	0.01	<0.01
Zinc	mg/L	0.005	0.077
Zirconium	mg/L	0.003	<0.003
Antimony	mg/L	0.0001	<0.0001
Arsenic	mg/L	0.0001	0.0001
Beryllium	mg/L	0.0001	<0.0001
Cadmium	mg/L	0.000015	0.000033
Chromium	mg/L	0.001	<0.0010
Cobalt	mg/L	0.0001	0.0002
Copper	mg/L	0.0001	0.0209
Lead	mg/L	0.00002	0.00096



COC #: DWTE231020

Report To:

Tatham Engineering

DATE SUBMITTED:

DATE REPORTED:

SAMPLE MATRIX:

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

20-Oct-23 27-Oct-23

Drinking Water

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

CUSTOMER PROJECT: 123016

P.O. NUMBER:

WATERWORKS NO:

	Client ID:		DW2			
	Sample ID:		23-029437-2			
	Date Collected:	Date Collected:				
Molybdenum	mg/L	0.0001	0.0001			
Selenium	mg/L	0.001	<0.001			
Silver	mg/L	0.0001	<0.0001			
Thallium	mg/L	0.00005	<0.00005			
Uranium	mg/L	0.00005	0.00022			
Vanadium	mg/L	0.0001	<0.0001			

R.L. = Reporting Limit

The analytical results reported herein refer to the samples as received. Reproduction of this analytical report in full or in part is prohibited without prior written consent from Caduceon Environmental Laboratories.

T 705-444-2565 **E** info@tathameng.com

tathameng.com



File 123016

February 8, 2023

Troy and Laura Allen 476537 3rd Line Melancthon Township, Ontario, L9V 1T4 troy@troysgarage.com

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mr. and Mrs. Allen:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to initiate a domestic water well monitoring program as part of the due diligence investigation process associated with the on-going domestic water well monitoring program for the Shelburne Quarry.

On February 8, 2023, Tatham installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument used to automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

Manual groundwater levels were measured at depths of 1.2 and 1.4 m below existing grade on May 24 and October 17, 2023, respectively. A hydrograph illustrating the continuous groundwater levels in your well over the course of a year of monitoring is provided for reference. The downward spikes illustrate typical household water usage.

On October 17, 2023, a water sample was taken from your outside faucet, as this typically bypasses any filtration you may have. Results from this sample have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 279 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.

The operational guideline for hardness is set between 80 to 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water too





Troy and Laura Allen

soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO₃) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.


Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo. Group Lead - Hydrogeology

JRM/AK:ha

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\2023 Letter\DW1\L - 476537 3rd Line - DW Monitoring Program Letter.docx





REPORT NO: 23-029437 Rev1 COC #: DWTE231020

Report To:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

DATE SUBMITTED: 20-Oct-23 CUSTOMER PROJECT: 123016

DATE REPORTED: 27-Oct-23 P.O. NUMBER: SAMPLE MATRIX: Drinking Water WATERWORKS NO:

	Client ID:		DW1
	Sample ID:		23-029437-1
	Date Collected:		17-Oct-23
Parameter	Units	R.L.	
Alkalinity(CaCO3) to pH4.5	mg/L	5	278
Bicarbonate (as CaCO3)	mg/L	5	278
pH @25°C	pH units		8.16
Conductivity @25°C	uS/cm	1	636
Chloride	mg/L	0.5	29.8
Nitrate (N)	mg/L	0.05	2.34
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	17
Phosphorus (Total)	mg/L	0.01	<0.01
Total Kjeldahl Nitrogen	mg/L	0.1	<0.1
Hardness (as CaCO3)	mg/L as CaCO3	0.02	279
Aluminum	mg/L	0.01	0.05
Barium	mg/L	0.001	0.04
Bismuth	mg/L	0.02	<0.02
Boron	mg/L	0.005	0.009
Calcium	mg/L	0.02	79.8
Iron	mg/L	0.005	0.005
Lithium	mg/L	0.005	<0.005
Magnesium	mg/L	0.02	19.4
Manganese	mg/L	0.001	0.001
Nickel	mg/L	0.01	<0.01
Potassium	mg/L	0.1	1.6
Silicon	mg/L	0.01	3.65
Silica	mg/L	2	8
Sodium	mg/L	0.2	14
Strontium	mg/L	0.001	0.13
Tin	mg/L	0.05	<0.05
Titanium	mg/L	0.005	<0.005
Tungsten	mg/L	0.01	<0.01
Zinc	mg/L	0.005	0.108
Zirconium	mg/L	0.003	< 0.003
Antimony	mg/L	0.0001	<0.0001
Arsenic	mg/L	0.0001	0.0002
Beryllium	mg/L	0.0001	<0.0001
Cadmium	mg/L	0.000015	0.000074
Chromium	mg/L	0.001	<0.0010
Cobalt	mg/L	0.0001	0.0002
Copper	mg/L	0.0001	0.0381
Lead	mg/L	0.00002	0.00095



COC #: DWTE231020

Report To:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan **CADUCEON Environmental Laboratories**

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

DATE SUBMITTED:	20-Oct-23	CUSTOMER PROJECT: 123016	
DATE REPORTED:	27-Oct-23	P.O. NUMBER:	
SAMPLE MATRIX:	Drinking Water	WATERWORKS NO:	

	Client ID:		DW1
	Sample ID:		23-029437-1
	Date Collected:		17-Oct-23
Molybdenum	mg/L	0.0001	0.0005
Selenium	mg/L	0.001	<0.001
Silver	mg/L	0.0001	<0.0001
Thallium	mg/L	0.00005	<0.00005
Uranium	mg/L	0.00005	0.00059
Vanadium	mg/L	0.0001	<0.0001

R.L. = Reporting Limit

The analytical results reported herein refer to the samples as received. Reproduction of this analytical report in full or in part is prohibited without prior written consent from Caduceon Environmental Laboratories.





File 123016

February 9, 2024

Kevin McGriskin 477084 3rd Line Melancthon Township, Ontario, L9V 1S6 kevinmcariskin@hotmail.com

Re: Strada Aggregates, Shelburne Quarry Domestic Well Monitoring Program

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to initiate a domestic water well monitoring program as part of the due diligence investigation process associated with the on-going domestic water well monitoring program for the Shelburne Quarry.

In January 2023, Tatham took over the monitoring of the level datalogger in your drilled well, as a part of the monitoring program at the Strada Quarry. A water level datalogger is an instrument used to automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

Manual groundwater levels were measured at depths of 20.3 and 18.5 m below existing grade on May 24 and October 17, 2023, respectively. A hydrograph illustrating the continuous groundwater levels in your well over the course of a year of monitoring is provided for reference. The downward spikes illustrate typical household water usage.

On October 17, 2023, a water sample was taken from your outside faucet, as this typically bypasses any filtration that you may have. Results from this sample have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of lead, and hardness with a measured concentration of 0.0269mg/L and 279 mg/L respectively. The ODWQS maximum acceptable concentration for lead has been listed at 0.01 mg/L and the ODWQS Operational Guideline for hardness has been set at 80 to 100 mg/L.

As lead is considered a health based ODWQS you were notified by Tatham of the lead exceedance on November 27, 2023, and Tatham scheduled a re-sample to confirm the elevated Lead concentrations. Tatham returned on November 30, 2023 and retrieved an untreated water sample from your tap. The second sample was submitted for chemical testing of lead only, and the results indicated the Lead concentrations were well below the applicable ODWQS. Based on the results of the second sample it can



Authorized by the Association of Professional Engineers

of Ontario to offer professional engineering services.



be concluded with a high degree of confidence that there is no threat at the point of consumption, but we would recommend not drinking water from the outside tap.

The operational guideline for hardness is set between 80 to 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water too soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO₃) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,


Tatham Engineering Limited

Alleia Kimberley, MSc., P.Geo. Group Leader - Hydrogeology

JRM/AK:ha

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\2023 Letter\DW3\L - 477084 3rd Line - DW Monitoring Program Letter.docx







REPORT NO: 23-029437 Rev3 COC #: DWTE231020

Report To:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

DATE SUBMITTED: 20-Oct-23 DATE REPORTED: 27-Oct-23

SAMPLE MATRIX: **Drinking Water**

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

CUSTOMER PROJECT: 123016	
P.O. NUMBER:	
MATERIMORKS NO:	

	Client ID:		DW3
	Sample ID:		23-029437-3
	Date Collected:		17-Oct-23
Parameter	Units	R.L.	
Alkalinity(CaCO3) to pH4.5	mg/L	5	244
Bicarbonate (as CaCO3)	mg/L	5	244
pH @25°C	pH units		8.04
Conductivity @25°C	uS/cm	1	562
Chloride	mg/L	0.5	10.9
Nitrate (N)	mg/L	0.05	7.61
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	22
Phosphorus (Total)	mg/L	0.01	<0.01
Total Kjeldahl Nitrogen	mg/L	0.1	<0.1
Hardness (as CaCO3)	mg/L as CaCO3	0.02	268
Aluminum	mg/L	0.01	0.05
Barium	mg/L	0.001	0.055
Bismuth	mg/L	0.02	<0.02
Boron	mg/L	0.005	0.007
Calcium	mg/L	0.02	73
Iron	mg/L	0.005	0.023
Lithium	mg/L	0.005	<0.005
Magnesium	mg/L	0.02	20.8
Manganese	mg/L	0.001	0.001
Nickel	mg/L	0.01	<0.01
Potassium	mg/L	0.1	1.4
Silicon	mg/L	0.01	3.93
Silica	mg/L	2	8
Sodium	mg/L	0.2	3.3
Strontium	mg/L	0.001	0.157
Tin	mg/L	0.05	<0.05
Titanium	mg/L	0.005	<0.005
Tungsten	mg/L	0.01	<0.01
Zinc	mg/L	0.005	1.73
Zirconium	mg/L	0.003	<0.003
Antimony	mg/L	0.0001	0.0002
Arsenic	mg/L	0.0001	0.0003
Beryllium	mg/L	0.0001	<0.0001
Cadmium	mg/L	0.000015	0.000131
Chromium	mg/L	0.001	<0.0010
Cobalt	mg/L	0.0001	0.0001
Copper	mg/L	0.0001	0.0205
Lead	mg/L	0.00002	0.0269



COC #: DWTE231020

Report To:

Tatham Engineering

DATE SUBMITTED:

DATE REPORTED:

SAMPLE MATRIX:

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

20-Oct-23 27-Oct-23

Drinking Water

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

CUSTOMER PROJECT: 123016

P.O. NUMBER:

WATERWORKS NO:

	Client ID:		DW3	
	Sample ID:		23-029437-3	
	Date Collected:	Date Collected:		
Molybdenum	mg/L	0.0001	0.0007	
Selenium	mg/L	0.001	<0.001	
Silver	mg/L	0.0001	<0.0001	
Thallium	mg/L	0.00005	<0.00005	
Uranium	mg/L	0.00005	0.00067	
Vanadium	mg/L	0.0001	<0.0001	

R.L. = Reporting Limit

The analytical results reported herein refer to the samples as received. Reproduction of this analytical report in full or in part is prohibited without prior written consent from Caduceon Environmental Laboratories.

C A D U C E N° N° ENVIRONMENTAL LABORATORIES Client committed, Quality assured, Canadian owned.

CERTIFICATE OF ANALYSIS

123016

Final Report

C.O.C.: DW112379 REPORT No: 23-033605 - Rev. 0

Report To:

Tatham Engineering
115 Sandford Fleming Drive

Suite 200

Collingwood, ON L9Y 5A6

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8

Attention: Alicia Kimberley

DATE RECEIVED: 2023-Nov-30

2023-Nov-30 CUSTOMER PROJECT: 2023-Dec-04 P.O. NUMBER:

SAMPLE MATRIX: Drinking Water

Analyses Qty Site Analyzed Authorized Date Analyzed Lab Method Reference Method ICP/MS (Liquid) 1 OTTAWA AOZKAYMAK 2023-Dec-04 D-ICPMS-01 EPA 200.8

R.L. = Reporting Limit
NC = Not Calculated

DATE REPORTED:

Test methods may be modified from specified reference method unless indicated by an *

				Client I.D.	477084 3rd Line
				Sample I.D.	23-033605-1
				Date Collected	2023-Nov-29
Parameter	Units	R.L.	Limits	DWG	-
Lead	mg/L	0.00002	0.010	MAC	0.00017

DWG - Drinking Water Guidelines

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective

OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

Michelle Dubien Data Specialist

tathameng.com



File 123016

February 9, 2024

Rick Wallace 635007 Side Road 15 Melancthon Township, Ontario, LON 1S6

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mr. Wallace:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to initiate a domestic water well monitoring program as part of the due diligence investigation process associated with the on-going domestic water well monitoring program for the Shelburne Quarry.

On October 4, 2023, Tatham installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument used to automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

Manual groundwater levels were measured at depths of 9.1 and 9.0 m below existing grade on October 4 and October 17, 2023, respectively. A hydrograph illustrating the continuous groundwater levels in your well over the course of a year of monitoring is provided for reference. The downward spikes illustrate typical household water usage.

On October 17, 2023, a water sample was taken from your outside faucet, as this typically bypasses any filtration that you may have. Results from this sample have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 323 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.

The operational guideline for hardness is set between 80 to 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water too soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO₃) is considered an acceptable balance between corrosion and incrustation.





Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.


Yours truly,

Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo. Group Leader - Hydrogeology JRM/AK:ha

 $\label{localization} I:\2023\ Projects\123016\ -\ Strada\ -\ Shelburne\04\ -\ ARA\ Submission\Documents\Reports\Domestic\ Well\ Reports\2023\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW\ Monitoring\ Program\ Letter\DW5\L\ -\ 625007\ Side\ Road\ 15\ -\ DW5\L\ -\ BW5\L\ -$





COC #: DWTE231020

Report To:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan **CADUCEON Environmental Laboratories**

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

DATE SUBMITTED:	20-Oct-23	CUSTOMER PROJECT: 123016	
DATE REPORTED:	27-Oct-23	P.O. NUMBER:	
SAMPLE MATRIX:	Drinking Water	WATERWORKS NO:	

	Client ID:		DW5
	Sample ID:		23-029437-5
	Date Collected:		17-Oct-23
Parameter	Units	R.L.	
Alkalinity(CaCO3) to pH4.5	mg/L	5	294
Bicarbonate (as CaCO3)	mg/L	5	294
pH @25°C	pH units		8.08
Conductivity @25°C	uS/cm	1	703
Chloride	mg/L	0.5	26.6
Nitrate (N)	mg/L	0.05	9.8
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	18
Phosphorus (Total)	mg/L	0.01	0.02
Total Kjeldahl Nitrogen	mg/L	0.1	<0.1
Hardness (as CaCO3)	mg/L as CaCO3	0.02	323
Aluminum	mg/L	0.01	0.07
Barium	mg/L	0.001	0.023
Bismuth	mg/L	0.02	<0.02
Boron	mg/L	0.005	0.016
Calcium	mg/L	0.02	83.9
Iron	mg/L	0.005	0.007
Lithium	mg/L	0.005	<0.005
Magnesium	mg/L	0.02	27.6
Manganese	mg/L	0.001	0.002
Nickel	mg/L	0.01	<0.01
Potassium	mg/L	0.1	4.2
Silicon	mg/L	0.01	2.79
Silica	mg/L	2	6
Sodium	mg/L	0.2	6.4
Strontium	mg/L	0.001	0.087
Tin	mg/L	0.05	<0.05
Titanium	mg/L	0.005	<0.005
Tungsten	mg/L	0.01	<0.01
Zinc	mg/L	0.005	0.187
Zirconium	mg/L	0.003	< 0.003
Antimony	mg/L	0.0001	<0.0001
Arsenic	mg/L	0.0001	0.0002
Beryllium	mg/L	0.0001	<0.0001
Cadmium	mg/L	0.000015	0.000049
Chromium	mg/L	0.001	<0.0010
Cobalt	mg/L	0.0001	0.0002
Copper	mg/L	0.0001	0.0533
Lead	mg/L	0.00002	0.00091



COC #: DWTE231020

Report To:

Attention:

DATE SUBMITTED:

DATE REPORTED:

SAMPLE MATRIX:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Oliver Lestyan

20-Oct-23

27-Oct-23 **Drinking Water** **CADUCEON Environmental Laboratories**

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

CUSTOMER PROJECT: 123016	
P.O. NUMBER:	

WATERWORKS NO:	
DWE	

	Client ID:		DW5
	Sample ID:		23-029437-5
	Date Collected:		17-Oct-23
Molybdenum	mg/L	0.0001	<0.0001
Selenium	mg/L	0.001	<0.001
Silver	mg/L	0.0001	<0.0001
Thallium	mg/L	0.00005	<0.00005
Uranium	mg/L	0.00005	0.00019
Vanadium	mg/L	0.0001	0.0002

R.L. = Reporting Limit

The analytical results reported herein refer to the samples as received. Reproduction of this analytical report in full or in part is prohibited without prior written consent from Caduceon Environmental Laboratories.

tathameng.com



File 123016

February 9, 2024

Debbie Fawcett 625293 15th Side Road Melancthon Township, Ontario, L0N 1S6 Debbie.fawcett@sympatico.ca

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mrs. Fawcett:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to initiate a domestic water well monitoring program as part of the due diligence investigation process associated with the on-going domestic water well monitoring program for the Shelburne Quarry.

In January 2023, Tatham took over the monitoring of the level datalogger in your drilled well, as a part of the monitoring program at the Strada Quarry. A water level datalogger is an instrument used to automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

Manual groundwater levels were measured at depths of 5.4 and 5.2 m below existing grade on May 24 and October 17, 2023, respectively. A hydrograph illustrating the continuous groundwater levels in your well over the course of a year of monitoring is provided for reference. The downward spikes illustrate typical household water usage.

On October 17, 2023, a water sample was taken from your outside faucet, as this typically bypasses any filtration that you may have. Results from this sample have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 284 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.

The operational guideline for hardness is set between 80 to 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water too





Debbie Fawcett

2

soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO₃) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.


Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo. Group Leader - Hydrogeology

JRM/AK:ha







REPORT NO: 23-029437 Rev4 COC #: DWTE231020

CADUCEON Environmental Laboratories

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

Report To: Tatham Engineering 115 Sandford Fleming Drive

Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan

DATE SUBMITTED: 20-Oct-23 CUSTOMER PROJECT: 123016

DATE REPORTED: 27-Oct-23 P.O. NUMBER: SAMPLE MATRIX: Drinking Water WATERWORKS NO:

	Client ID:		DW4
	Sample ID:		23-029437-4
	Date Collected:		17-Oct-23
Parameter	Units	R.L.	
Alkalinity(CaCO3) to pH4.5	mg/L	5	265
Bicarbonate (as CaCO3)	mg/L	5	265
pH @25°C	pH units		8.05
Conductivity @25°C	uS/cm	1	609
Chloride	mg/L	0.5	12.2
Nitrate (N)	mg/L	0.05	8.17
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	22
Phosphorus (Total)	mg/L	0.01	<0.01
Total Kjeldahl Nitrogen	mg/L	0.1	<0.1
Hardness (as CaCO3)	mg/L as CaCO3	0.02	284
Aluminum	mg/L	0.01	0.05
Barium	mg/L	0.001	0.023
Bismuth	mg/L	0.02	<0.02
Boron	mg/L	0.005	0.015
Calcium	mg/L	0.02	76.8
Iron	mg/L	0.005	<0.005
Lithium	mg/L	0.005	<0.005
Magnesium	mg/L	0.02	22.5
Manganese	mg/L	0.001	<0.001
Nickel	mg/L	0.01	<0.01
Potassium	mg/L	0.1	2.2
Silicon	mg/L	0.01	3.12
Silica	mg/L	2	7
Sodium	mg/L	0.2	3.2
Strontium	mg/L	0.001	0.089
Tin	mg/L	0.05	<0.05
Titanium	mg/L	0.005	<0.005
Tungsten	mg/L	0.01	<0.01
Zinc	mg/L	0.005	0.141
Zirconium	mg/L	0.003	< 0.003
Antimony	mg/L	0.0001	<0.0001
Arsenic	mg/L	0.0001	0.0001
Beryllium	mg/L	0.0001	<0.0001
Cadmium	mg/L	0.000015	0.000067
Chromium	mg/L	0.001	<0.0010
Cobalt	mg/L	0.0001	0.0002
Copper	mg/L	0.0001	0.137
Lead	mg/L	0.00002	0.0037



COC #: DWTE231020

Report To:

Tatham Engineering

115 Sandford Fleming Drive Collingwood, ON L9Y 5A6

Attention: Oliver Lestyan **CADUCEON Environmental Laboratories**

112 Commerce Park Dr Unit L

Barrie, ON L4N 8W8 Tel: 705-252-5743

DATE SUBMITTED:	20-Oct-23	CUSTOMER PROJECT: 123016	
DATE REPORTED:	27-Oct-23	P.O. NUMBER:	
SAMPLE MATRIX:	Drinking Water	WATERWORKS NO:	

	Client ID: Sample ID: Date Collected:		DW4
			23-029437-4
			17-Oct-23
Molybdenum	mg/L	0.0001	0.0005
Selenium	mg/L	0.001	<0.001
Silver	mg/L	0.0001	<0.0001
Thallium	mg/L	0.00005	<0.00005
Uranium	mg/L	0.00005	0.0004
Vanadium	mg/L	0.0001	<0.0001

R.L. = Reporting Limit

The analytical results reported herein refer to the samples as received. Reproduction of this analytical report in full or in part is prohibited without prior written consent from Caduceon Environmental Laboratories.

tathameng.com



File 123016

March 30, 2023

Troy and Laura Allen 476537 3rd Line Melancthon, Ontario L9V 1T4

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mr. and Mrs. Allen:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to continue the on-going domestic water well monitoring program for the Shelburne Quarry. Whitewater Hydrogeology Ltd (Whitewater), which as of January 2023 has fully integrated with Tatham, previously carried out the domestic water well monitoring program.

On February 8th, 2023, Tatham installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument that automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

A hydrograph illustrating the measured groundwater levels in your well over the course of a year of monitoring will be provided annually. Given the data logger was only installed in February 2023 a hydrograph was not generated as part of this summary letter but will be provided in next years summary letter.

On February 8th, 2023, a water sample was taken from your well and tested for various parameters. Results have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of Lead with a measured concentration of 41.3 μ g/L compared to a health based ODWQS Maximum Allowable Concentration of 10 μ g/L, and Iron with a measured concentration of 1900 μ g/L compared to an ODWQS Aesthetic Objective of 300 μ g/L.

As Lead is considered a health based ODWQS you were notified by Tatham immediately upon receipt of the laboratory results, and Tatham scheduled a re-sample to confirm the elevated Lead concentrations. Tatham returned on February 27, 2023 and retrieved an untreated water sample from your tap. The second sample was submitted for chemical testing of Lead only, and the results indicated the Lead





concentrations were well below the applicable ODWQS. Based on the results of the second sample it is suspected the original measured Lead concentrations were anomalous.

With respect to the elevated Iron concentrations, high iron levels are very common in Ontario. Iron is usually a result of mineral deposits present in groundwater. The standard found in ODWQS is an aesthetic objective and does not pose a threat to your health. High levels of iron can stain clothing, plumbing fixtures or give the water an unpleasant colour. Treatment options such as ferric sulfate can be effective in removing iron if it is of concern to you.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,

Tatham Engineering Limited

Alidia Kimberley, MSc., P.Geo Group Lead - Hydrogeology

JRM/AK/DT:ha

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\Strada Letters\DW1\L - Allen (DW1) 2023.docx

Daniel Twigger, B.Sc.Eng., P.Eng.

Manager - Water Resources Engineering





Supersedes report printed: 03/21/2023 12:15

Client: Jordan Miller Work Order Number: 490466

Company: Tatham Engineering Limited PO #:

Address: 115 Sandford Fleming Drive, Suite 200 Regulation: ODWS

Collingwood, ON, L9Y 5A6 Project #:

Phone: DWS #:

Email: jmiller@tathameng.com Sampled By: Jordan Miller

Date Order Received: 2/10/2023 Analysis Started: 2/10/2023
Arrival Temperature: 13.2 °C Analysis Completed: 2/17/2023

WORK ORDER SUMMARY

Date of Issue: 03/21/2023 16:34

ANALYSES WERE PERFORMED ON THE FOLLOWING SAMPLES. THE RESULTS RELATE ONLY TO THE ITEMS TESTED.

Sample Description	Lab ID	Matrix	Туре	Comments	Date Collected	Time Collected
476537 3rd Line (Alen)	1850151	Ground Water	None	SAMPLE CONTAINED RESULT EXCEEDENCES.	2/8/2023	1:05 PM

METHODS AND INSTRUMENTATION

THE FOLLOWING METHODS WERE USED FOR YOUR SAMPLE(S):

Method	Lab	Description	Reference
Alkalinity (A1.0)	Mississauga	Determination of Alkalinity by Titration	Modified from APHA-2320B
Anions Water (mg/L by IC) (A5)	Mississauga	Determination of Anions in Water by Ion Chromatography	Modified from SW846-9056A
Carbonate (A94)	Mississauga	Determination of Carbonate and Bi-Carbonate	Modified from APHA-2320
Conductivity of Water (A12)	Mississauga	Determination of Conductivity in Water at 25°C	Modified from SM 2510 B
ICPMS Reg. Water (A13)	Mississauga	Determination of Metals in Water by ICP/MS	Modified from SW846-6020
pH of Water (A2.0)	Mississauga	Determination of Water pH by Ion Selective Electrode	Modified from APHA-4500H+ B
TDS (A27)	Mississauga	Determination of Total Dissolved Solids in water by gravimetry	Modified from SM-2540
TKN Water Dig. (A58)	Kirkland Lake	Determination of Total Kjeldahl Nitrogen in Waters with Block Digestion.	Modified from SM-4500 NORG-D
TP Water (A23.2)	Kirkland Lake	Determination of Total Phosphorus in Water.	Modified from EPA 365.3 and ESS 310.2,



Supersedes report printed: 03/21/2023 12:15

Tatham Engineering Limited Work Order Number: 490466

REPORT COMMENTS

Report revised to include retest data for ICMPS (Pb) as per Cl 20426 02/21/23 YH Report revised to add comparative regulation (ODWS) as per Cl 20534 03/21/23 YH

This report has been approved by:

Date of Issue: 03/21/2023 16:34

Marc Creighton

Laboratory Director

Supersedes report printed: 03/21/2023 12:15

Tatham Engineering Limited

Work Order Number: 490466

WORK ORDER RESULTS

Date of Issue: 03/21/2023 16:34

Sample Description	476537 3rd Li	. ,		
Sample Date/Time	2/8/2023 1:			
Lab ID	18501			
Anions	Result	MDL	Units	Criteria: ODWS
Chloride	31.1	0.2	mg/L	250
Nitrate (as N)	2.59	0.05	mg/L	10
Nitrite (as N)	<0.05	0.05	mg/L	1
Sulphate	17.8	0.3	mg/L	500
General Chemistry	Result	MDL	Units	Criteria: ODWS
Bicarbonate (Calc.)	251	1	mg/L as CaCO3	~
Conductivity	605	1	μS/cm	~
M-Alkalinity (pH 4.5)	253	2	mg/L as CaCO3	~
рН	7.88	N/A	рН	~
Total Kjeldahl Nitrogen	1.7	0.4	mg/L	~
Total Phosphorus (as P)	0.006	0.002	mg/L	~
Metals	Result	MDL	Units	Criteria: ODWS
Aluminum	<1	1	ug/L	100
Antimony	<0.5	0.5	ug/L	6
Arsenic	<1	1	ug/L	10
Barium	49	1	ug/L	1000
Beryllium	<0.5	0.5	ug/L	~
Bismuth	<1	1	ug/L	~
Boron	7	2	ug/L	5000
Cadmium	0.3	0.1	ug/L	5
Calcium	82600	500	ug/L	~
Cerium	<1	1	ug/L	~
Cesium	<1	1	ug/L	~
Chromium	6	1	ug/L	50



Supersedes report printed: 03/21/2023 12:15

Tatham Engineering Limited

Date of Issue: 03/21/2023 16:34

Cobalt	0.2	0.1	ug/L	~
Copper	3	1	ug/L	1000
Europium	<1	1	ug/L	~
Gallium	1	1	ug/L	~
Iron	1900	200	ug/L	300
Lanthanum	<1	1	ug/L	~
Lead	26.9	0.1	ug/L	10
Lead [rr]	41.3	0.1	ug/L	10
Lithium	<5	5	ug/L	~
Magnesium	20300	5	ug/L	~
Manganese	34	1	ug/L	50
Mercury	<0.1	0.1	ug/L	1
Molybdenum	<1	1	ug/L	~
Nickel	4	1	ug/L	~
Niobium	<1	1	ug/L	~
Phosphorus	<50	50	ug/L	~
Potassium	2120	100	ug/L	~
Rhodium	<1	1	ug/L	~
Rubidium	2	1	ug/L	~
Scandium	<1	1	ug/L	~
Selenium	<0.5	0.5	ug/L	50
Silicon	4400	600	ug/L	~
Silver	<0.1	0.1	ug/L	~
Sodium	14300	100	ug/L	20000
Strontium	127	1	ug/L	~
Sulfur	5300	800	ug/L	~
Tellurium	<1	1	ug/L	~
Thallium	<0.1	0.1	ug/L	~
Thorium	<1	1	ug/L	~

Work Order Number: 490466



Supersedes report printed: 03/21/2023 12:15

Tatham Engineering Limited

Metals	Result	MDL	Units	Criteria: ODWS
Tin	<1	1	ug/L	~
Titanium	2	1	ug/L	~
Tungsten	<1	1	ug/L	~
Uranium	<1	1	ug/L	20
Vanadium	2	1	ug/L	~
Yttrium	<1	1	ug/L	~
Zinc	175	1	ug/L	5000
Zirconium	<1	1	ug/L	~
Solids	Result	MDL	Units	Criteria: ODWS
Total Dissolved Solids	387 [382]	2	mg/L	500

LEGEND

Dates: Dates are formatted as mm/dd/year throughout this report.

MDL: Method detection limit or minimum reporting limit.

Date of Issue: 03/21/2023 16:34

[]: Results for laboratory replicates are shown in square brackets immediately below the associated sample result for ease of comparison.

~: In a criteria column indicates the criteria is not applicable for the parameter row.

Quality Control: All associated Quality Control data is available on request.

Exceedences: HIGHLIGHTED CELLS INDICATE THAT THE RESULT EXCEEDS A REGULATORY LIMIT. CALCULATED UNCERTAINTY ESTIMATIONS ARE NOT APPLIED FOR DETERMINING SAMPLE EXCEEDANCES.

Field Data: Reports containing Field Parameters represent data that has been collected and provided by the client. Testmark is not responsible for the validity of this data which may be used in subsequent calculations.

Sample Condition Deviations: A noted sample condition deviation may affect the validity of the result. Results apply to the sample(s) as received.

Reproduction of Report: Report shall not be reproduced, except in full, without the approval of Testmark Laboratories Ltd.

ICPMS Dustfall Insoluble: The ICPMS Dustfall Insoluble Portion method analyzes only the particulate matter from the Dustfall Sampler which is retained on the analysis filter during the Dustfall method.

Regulation Comparisons: Disclaimer: Please note that regulation criteria are provided for comparative purposes, however the onus on ensuring the validity of this comparison rests with the client.

Work Order Number: 490466



Final Report

C.O.C.: DW122568 REPORT No. B23-02307

Report To:

Caduceon Environmental Laboratories

Tatham Engineering 115 Sandford Fleming Drive, Suite 200 112 Commerce Park Drive Barrie ON L4N 8W8

Collingwood ON L9Y 5A6

Tel: 705-252-5743

Attention: Tecia White

Fax: 705-252-5746

DATE RECEIVED: 03-Mar-23

JOB/PROJECT NO.:

DATE REPORTED: 07-Mar-23

P.O. NUMBER:

SAMPLE MATRIX: Drinking Water

WATERWORKS NO.

		ſ	Client I.D.:		476537 3rd		ODWS	
			Sample I.D.:		Line			Type of
					B23-02307-1		Objective	Objective
			Date Collected:		27-Feb-23			
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed		•	•	
Lead	mg/L	0.00002	EPA 200.8	07-Mar-23/O	0.00067		0.01	MAC

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit

Test methods may be modified from specified reference method unless indicated by an *

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager

T 705-444-2565 **E** info@tathameng.com

tathameng.com



File 123016

April 4, 2023

Debbie Fawcett 625293 SR 15 Melancthon, Ontario L9V 1Z5

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mrs. Fawcett:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to continue the on-going domestic water well monitoring program for the Shelburne Quarry. Whitewater Hydrogeology Ltd (Whitewater), which as of January 2023 has fully integrated with Tatham, previously carried out the domestic water well monitoring program.

On October 4th, 2022, Whitewater installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument that automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

The water level data is presented in the hydrograph appended to this letter. The water level is shown in black and has been calibrated to the manual measurement taken at the time the datalogger device was installed. A complete year cycle of groundwater monitoring is not available yet for your well; however, the limited water level data collected to date shows two different trends; 1) a seasonal response: the slow decline in water levels during the fall months; 2) daily trends: the instantaneous drawdown and recovery because of the daily water use and pump activation. These downward spikes in the data represent the times your well is in operation and supplying water to your home and are completely normal. The data suggests that the well has sufficient supply for domestic use.

On October 4th, 2022, a groundwater sample was taken from your water well and tested for various parameters. Results have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.



The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 312 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.

The operational guideline for hardness is set between 80 and 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water that is too soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO3) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo.

Group Lead - Hydrogeology


JRM/AK/DT:ha

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\Strada Letters\DW4\L - Fawcett (DW4)

Daniel Twigger, B.Sc.Eng., P.Eng.

Manager - Water Resources Engineering







Final Report

C.O.C.: G111051 REPORT No. B22-31359

Rev. 8

Report To:

Whitewater Hydrogeology Ltd

8537 36/37 Nottawasaga Side Rd, Collingwood Ontario L94 3Y9 Canada

Attention: Tecia White

DATE RECEIVED: 05-Oct-22

DATE REPORTED: 29-Mar-23
SAMPLE MATRIX: Groundwater

Caduceon Environmental Laboratories

285 Dalton Ave

Kingston Ontario K7K 6Z1

Tel: 613-544-2001 Fax: 613-544-2770

JOB/PROJECT NO.: Strada Domestic

P.O. NUMBER: WATERWORKS NO.

			Client I.D.:		#625293	OD	ws
			Sample I.D.:		B22-31359-4	Objection	Type of
			Date Collecte	d:	04-Oct-22	Objective	Objective
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed			
Alkalinity(CaCO3) to pH4.5	mg/L	5	SM 2320B	07-Oct-22/O	257	30-500	OG
Carbonate (as CaCO3)	mg/L	5	SM 2320B	07-Oct-22/O	< 5		
Bicarbonate(as CaCO3)	mg/L	5	SM 2320B	07-Oct-22/O	257		
Conductivity @25°C	µmho/cm	1	SM 2510B	07-Oct-22/O	606		
pH @25°C	pH Units		SM 4500H	07-Oct-22/O	7.95	6.5-8.5	OG
Chloride	mg/L	0.5	SM4110C	07-Oct-22/O	13.6	250	AO
Nitrite (N)	mg/L	0.1	SM4110C	07-Oct-22/O	< 0.1	1	MAC
Nitrate (N)	mg/L	0.1	SM4110C	07-Oct-22/O	9.0	10	MAC
Sulphate	mg/L	1	SM4110C	07-Oct-22/O	23	500	AO
Phosphorus-Total	mg/L	0.01	E3516.2	12-Oct-22/K	0.01		
Total Kjeldahl Nitrogen	mg/L	0.1	E3516.2	12-Oct-22/K	0.1		
TDS (Calc. from Cond.)	mg/L	1	Calc.	12-Oct-22	314	500	AO
Hardness (as CaCO3)	mg/L	1	SM 3120	11-Oct-22/O	312	500,80-100	ODWO,OG
Aluminum	mg/L	0.01	SM 3120	11-Oct-22/O	0.02	0.1	OG
Arsenic	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02	0.01	MAC
Boron	mg/L	0.005	SM 3120	11-Oct-22/O	0.014	5	MAC
Barium	mg/L	0.001	SM 3120	11-Oct-22/O	0.023	1	MAC
Beryllium	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002		
Bismuth	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02		
Calcium	mg/L	0.02	SM 3120	11-Oct-22/O	84.5		
Cadmium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005	0.005	MAC
Chromium	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002	0.05	MAC
Cobalt	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Copper	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002	1	AO

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit

Test methods may be modified from specified reference method unless indicated by an *

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager



Final Report

C.O.C.: G111051 REPORT No. B22-31359

Rev. 8

Report To:

Whitewater Hydrogeology Ltd

8537 36/37 Nottawasaga Side Rd, Collingwood Ontario L94 3Y9 Canada

Attention: Tecia White

DATE RECEIVED: 05-Oct-22

DATE REPORTED: 29-Mar-23
SAMPLE MATRIX: Groundwater

Caduceon Environmental Laboratories

285 Dalton Ave

Kingston Ontario K7K 6Z1

Tel: 613-544-2001 Fax: 613-544-2770

JOB/PROJECT NO.: Strada Domestic

P.O. NUMBER: WATERWORKS NO.

			Client I.D.:		#625293	OD	ws
			Sample I.D.:		B22-31359-4	Ohioativa	Type of
			Date Collecte	ed:	04-Oct-22	Objective	Objective
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed			
Iron	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005	0.3	AO
Lead	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02	0.01	MAC
Lithium	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Magnesium	mg/L	0.02	SM 3120	11-Oct-22/O	24.6		
Manganese	mg/L	0.001	SM 3120	11-Oct-22/O	< 0.001	0.05	AO
Molybdenum	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Nickel	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Phosphorus	mg/L	0.1	SM 3120	11-Oct-22/O	< 0.1		
Potassium	mg/L	0.1	SM 3120	11-Oct-22/O	2.6		
Silica	mg/L	0.02	SM 3120	11-Oct-22/O	6.93		
Silicon	mg/L	0.01	SM 3120	11-Oct-22/O	3.24		
Silver	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Sodium	mg/L	0.2	SM 3120	11-Oct-22/O	3.3	200,20	AO,WL
Strontium	mg/L	0.001	SM 3120	11-Oct-22/O	0.094		
Tin	mg/L	0.05	SM 3120	11-Oct-22/O	< 0.05		
Titanium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Tungsten	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Vanadium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Yttrium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Zinc	mg/L	0.005	SM 3120	11-Oct-22/O	0.062	5	AO

11-Oct-22/O

< 0.003

mg/L

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

Zirconium

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit

Test methods may be modified from specified reference method unless indicated by an *

0.003

SM 3120

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager

¹ Revised report to add guidelines as per client request.

tathameng.com



File 123016

April 4, 2023

Kevin McGriskin 477084 3rd Line Melancthon, Ontario LON 1S6

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mr. McGriskin:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to continue the on-going domestic water well monitoring program for the Shelburne Quarry. Whitewater Hydrogeology Ltd (Whitewater), which as of January 2023 has fully integrated with Tatham, previously carried out the domestic water well monitoring program.

On October 4th, 2022, Whitewater installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument that automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

The water level data is presented in the hydrograph appended to this letter. The water level is shown in black and has been calibrated to the manual measurement taken at the time the datalogger device was installed. A complete year cycle of groundwater monitoring is not available yet for your well; however, the limited water level data collected to date shows two different trends; 1) a seasonal response: the slow decline in water levels during the fall months; 2) daily trends: the instantaneous drawdown and recovery because of the daily water use and pump activation. These downward spikes in the data represent the times your well is in operation and supplying water to your home and are completely normal. The data suggests the well has sufficient supply for domestic use.

On October 4th, 2022, a groundwater sample was taken from your water well and tested for various parameters. Results have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 287 mg/L compared to an ODWQS Operational Guideline of





80 to 100 mg/L, and manganese with a measured concentration of 0.07 mg/L compared to an ODWQS Aesthetic Objective of 0.05 mg/L.

The operational guideline for hardness is set between 80 and 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water that is too soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO3) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

The aesthetic guideline for manganese in drinking water is set to 0.05 mg/L (ODWQS, 2006). Manganese found in higher concentrations then this can lead to black staining on laundry and fixtures and a foul taste in very excessive concentrations. Your water has only exceeded this aesthetic guideline by 0.02 mg/L and should offer little to no issues at this time. Levels should be monitored and if any staining occurs then you may want to consider treatment options.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo.

Group Lead - Hydrogeology

JRM/AK/DT:ha

Manager - Water Resources Engineering

Daniel Twigger, B.Sc.Eng, P.Eng.


2023.docx

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\Strada Letters\DW3\L - McGriskin (DW3)





DW3
Water Levels for 2022





Final Report

C.O.C.: G111051 REPORT No. B22-31359

Rev. 7

Report To:

Whitewater Hydrogeology Ltd

8537 36/37 Nottawasaga Side Rd, Collingwood Ontario L94 3Y9 Canada

Attention: Tecia White

DATE RECEIVED: 05-Oct-22

DATE REPORTED: 29-Mar-23
SAMPLE MATRIX: Groundwater

Caduceon Environmental Laboratories

285 Dalton Ave

Kingston Ontario K7K 6Z1

Tel: 613-544-2001 Fax: 613-544-2770

JOB/PROJECT NO.: Strada Domestic

P.O. NUMBER: WATERWORKS NO.

			Client I.D.:		#477084	ODWS	
			Sample I.D.:		B22-31359-3	Ohiostivo	Type of
			Date Collecte	d:	04-Oct-22	Objective	Objective
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed			
Alkalinity(CaCO3) to pH4.5	mg/L	5	SM 2320B	07-Oct-22/O	246	30-500	OG
Carbonate (as CaCO3)	mg/L	5	SM 2320B	07-Oct-22/O	< 5		
Bicarbonate(as CaCO3)	mg/L	5	SM 2320B	07-Oct-22/O	246		
Conductivity @25°C	µmho/cm	1	SM 2510B	07-Oct-22/O	564		
pH @25°C	pH Units		SM 4500H	07-Oct-22/O	7.95	6.5-8.5	OG
Chloride	mg/L	0.5	SM4110C	07-Oct-22/O	11.8	250	AO
Nitrite (N)	mg/L	0.1	SM4110C	07-Oct-22/O	< 0.1	1	MAC
Nitrate (N)	mg/L	0.1	SM4110C	07-Oct-22/O	7.4	10	MAC
Sulphate	mg/L	1	SM4110C	07-Oct-22/O	22	500	AO
Phosphorus-Total	mg/L	0.01	E3516.2	12-Oct-22/K	0.01		
Total Kjeldahl Nitrogen	mg/L	0.1	E3516.2	12-Oct-22/K	< 0.1		
TDS (Calc. from Cond.)	mg/L	1	Calc.	12-Oct-22	292	500	AO
Hardness (as CaCO3)	mg/L	1	SM 3120	11-Oct-22/O	287	500,80-100	ODWO,OG
Aluminum	mg/L	0.01	SM 3120	11-Oct-22/O	0.02	0.1	OG
Arsenic	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02	0.01	MAC
Boron	mg/L	0.005	SM 3120	11-Oct-22/O	0.008	5	MAC
Barium	mg/L	0.001	SM 3120	11-Oct-22/O	0.057	1	MAC
Beryllium	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002		
Bismuth	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02		
Calcium	mg/L	0.02	SM 3120	11-Oct-22/O	78.5		
Cadmium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005	0.005	MAC
Chromium	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002	0.05	MAC
Cobalt	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Copper	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002	1	AO

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit

Test methods may be modified from specified reference method unless indicated by an *

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager



Final Report

C.O.C.: G111051 REPORT No. B22-31359

Rev. 7

Report To:

Whitewater Hydrogeology Ltd

8537 36/37 Nottawasaga Side Rd, Collingwood Ontario L94 3Y9 Canada

Attention: Tecia White

DATE RECEIVED: 05-Oct-22

DATE REPORTED: 29-Mar-23
SAMPLE MATRIX: Groundwater

Caduceon Environmental Laboratories

285 Dalton Ave

Kingston Ontario K7K 6Z1

Tel: 613-544-2001 Fax: 613-544-2770

JOB/PROJECT NO.: Strada Domestic

P.O. NUMBER: WATERWORKS NO.

					#477084	ODWS	
			Sample I.D.:		B22-31359-3	Ohiostiva	Type of
			Date Collecte	ed:	04-Oct-22	<u>Objective</u>	Objective
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed		-	
Iron	mg/L	0.005	SM 3120	11-Oct-22/O	0.019	0.3	AO
Lead	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02	0.01	MAC
Lithium	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Magnesium	mg/L	0.02	SM 3120	11-Oct-22/O	22.2		
Manganese	mg/L	0.001	SM 3120	11-Oct-22/O	0.070	0.05	AO
Molybdenum	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Nickel	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Phosphorus	mg/L	0.1	SM 3120	11-Oct-22/O	< 0.1		
Potassium	mg/L	0.1	SM 3120	11-Oct-22/O	2.4		
Silica	mg/L	0.02	SM 3120	11-Oct-22/O	8.68		
Silicon	mg/L	0.01	SM 3120	11-Oct-22/O	4.06		
Silver	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Sodium	mg/L	0.2	SM 3120	11-Oct-22/O	3.5	200,20	AO,WL
Strontium	mg/L	0.001	SM 3120	11-Oct-22/O	0.172		
Tin	mg/L	0.05	SM 3120	11-Oct-22/O	< 0.05		
Titanium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Tungsten	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01		
Vanadium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Yttrium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Zinc	mg/L	0.005	SM 3120	11-Oct-22/O	0.074	5	AO
Zirconium	mg/L	0.003	SM 3120	11-Oct-22/O	< 0.003		

Revised report to add guidelines as per client request.

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit

Test methods may be modified from specified reference method unless indicated by an *

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager





File 123016

April 4, 2023

Dan and Jennifer Robertson 1 Ashlea Lane Melancthon, Ontario L9V 3M9

Re: Strada Aggregates, Shelburne Quarry

Domestic Well Monitoring Program

Dear Mr. and Mrs. Robertson:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to continue the on-going domestic water well monitoring program for the Shelburne Quarry. Whitewater Hydrogeology Ltd (Whitewater), which as of January 2023 has fully integrated with Tatham, previously carried out the domestic water well monitoring program.

On October 4th, 2022, Whitewater installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument that automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

The water level data is presented in the hydrograph appended to this letter. The water level is shown in black and has been calibrated to the manual measurement taken at the time the datalogger device was installed. A complete year cycle of groundwater monitoring is not available yet for your well; however, the limited water level data collected to date shows two different trends; 1) a seasonal response: the slow decline in water levels during the fall months; 2) daily trends: the instantaneous drawdown and recovery because of the daily water use and pump activation. These downward spikes in the data represent the times your well is in operation and supplying water to your home and are completely normal. The data suggests that the well has sufficient supply for domestic use.

On October 4th, 2022, a groundwater sample was taken from your water well and tested for various parameters. Results have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 303 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.

The operational guideline for hardness is set between 80 and 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium





Mr. and Mrs. Robertson

carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water that is too soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO3) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo.

Group Lead - Hydrogeology

JRM/AK/DT:ha

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\Strada Letters\DW2\L - Robertson (DW2) 2023.docx

Daniel Twigger, B.Sc.Eng., P.Eng.

Manager - Water Resources Engineering



Final Report

C.O.C.: G111051 REPORT No. B22-31359

Rev. 5

Report To:

Whitewater Hydrogeology Ltd

8537 36/37 Nottawasaga Side Rd, Collingwood Ontario L94 3Y9 Canada

Attention: Tecia White

DATE RECEIVED: 05-Oct-22

DATE REPORTED: 29-Mar-23
SAMPLE MATRIX: Groundwater

Caduceon Environmental Laboratories

285 Dalton Ave

Kingston Ontario K7K 6Z1

Tel: 613-544-2001 Fax: 613-544-2770

JOB/PROJECT NO.: Strada Domestic

P.O. NUMBER: WATERWORKS NO.

			Client I.D.:		1 Ashlea Lane	OD	ows
			Sample I.D.:		B22-31359-1		Type of
			Date Collecte	d:	04-Oct-22	Objective	Objective
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed			
Alkalinity(CaCO3) to pH4.5	mg/L	5	SM 2320B	07-Oct-22/O	275	30-500	OG
Carbonate (as CaCO3)	mg/L	5	SM 2320B	07-Oct-22/O	< 5		
Bicarbonate(as CaCO3)	mg/L	5	SM 2320B	07-Oct-22/O	275		
Conductivity @25°C	µmho/cm	1	SM 2510B	07-Oct-22/O	569		
pH @25°C	pH Units		SM 4500H	07-Oct-22/O	8.00	6.5-8.5	OG
Chloride	mg/L	0.5	SM4110C	07-Oct-22/O	11.1	250	AO
Nitrite (N)	mg/L	0.1	SM4110C	07-Oct-22/O	< 0.1	1	MAC
Nitrate (N)	mg/L	0.1	SM4110C	07-Oct-22/O	4.0	10	MAC
Sulphate	mg/L	1	SM4110C	07-Oct-22/O	13	500	AO
Phosphorus-Total	mg/L	0.01	E3516.2	12-Oct-22/K	0.01		
Total Kjeldahl Nitrogen	mg/L	0.1	E3516.2	12-Oct-22/K	< 0.1		
TDS (Calc. from Cond.)	mg/L	1	Calc.	12-Oct-22	295	500	AO
Hardness (as CaCO3)	mg/L	1	SM 3120	11-Oct-22/O	303	500,80-100	ODWO,OG
Aluminum	mg/L	0.01	SM 3120	11-Oct-22/O	0.03	0.1	OG
Arsenic	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02	0.01	MAC
Boron	mg/L	0.005	SM 3120	11-Oct-22/O	0.008	5	MAC
Barium	mg/L	0.001	SM 3120	11-Oct-22/O	0.032	1	MAC
Beryllium	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002		
Bismuth	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02		
Calcium	mg/L	0.02	SM 3120	11-Oct-22/O	86.5		
Cadmium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005	0.005	MAC
Chromium	mg/L	0.002	SM 3120	11-Oct-22/O	< 0.002	0.05	MAC
Cobalt	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005		
Copper	mg/L	0.002	SM 3120	11-Oct-22/O	0.013	1	AO

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit

Test methods may be modified from specified reference method unless indicated by an *

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager



Final Report

C.O.C.: G111051 REPORT No. B22-31359

Rev. 5

Report To:

Whitewater Hydrogeology Ltd

8537 36/37 Nottawasaga Side Rd, Collingwood Ontario L94 3Y9 Canada

Attention: Tecia White

DATE RECEIVED: 05-Oct-22

DATE REPORTED: 29-Mar-23
SAMPLE MATRIX: Groundwater

Caduceon Environmental Laboratories

285 Dalton Ave

Kingston Ontario K7K 6Z1

Tel: 613-544-2001 Fax: 613-544-2770

JOB/PROJECT NO.: Strada Domestic

P.O. NUMBER:

WATERWORKS NO.

			Client I.D.:		1 Ashlea Lane	OD	ODWS	
			Sample I.D.:		B22-31359-1	Ohioativa	Type of	
			Date Collecte	ed:	04-Oct-22	<u>Objective</u>	Objective	
Parameter	Units	R.L.	Reference Method	Date/Site Analyzed				
Iron	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005	0.3	AO	
Lead	mg/L	0.02	SM 3120	11-Oct-22/O	< 0.02	0.01	MAC	
Lithium	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01			
Magnesium	mg/L	0.02	SM 3120	11-Oct-22/O	21.1			
Manganese	mg/L	0.001	SM 3120	11-Oct-22/O	< 0.001	0.05	AO	
Molybdenum	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01			
Nickel	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01			
Phosphorus	mg/L	0.1	SM 3120	11-Oct-22/O	< 0.1			
Potassium	mg/L	0.1	SM 3120	11-Oct-22/O	1.3			
Silica	mg/L	0.02	SM 3120	11-Oct-22/O	8.00			
Silicon	mg/L	0.01	SM 3120	11-Oct-22/O	3.74			
Silver	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005			
Sodium	mg/L	0.2	SM 3120	11-Oct-22/O	3.6	200,20	AO,WL	
Strontium	mg/L	0.001	SM 3120	11-Oct-22/O	0.112			
Tin	mg/L	0.05	SM 3120	11-Oct-22/O	< 0.05			
Titanium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005			
Tungsten	mg/L	0.01	SM 3120	11-Oct-22/O	< 0.01			
Vanadium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005			
Yttrium	mg/L	0.005	SM 3120	11-Oct-22/O	< 0.005			
Zinc	mg/L	0.005	SM 3120	11-Oct-22/O	0.040	5	AO	
Zirconium	mg/L	0.003	SM 3120	11-Oct-22/O	< 0.003			

Revised report to add guidelines as per client request.

ODWS - Ontario Drinking Water Standards

AO - Aesthetic Objectives

IMAC - Interim Maximum Acceptable Concentration

MAC - Maximum Acceptable Concentration

ODWO - D-5-5 Objective OG - Operational Guidelines

WL - Warning Level - Sodium Restricted Diets

R.L. = Reporting Limit


Test methods may be modified from specified reference method unless indicated by an *

Site Analyzed=K-Kingston, W-Windsor, O-Ottawa, R-Richmond Hill, B-Barrie

Christine Burke Lab Manager



DW2
Water Levels for 2022



tathameng.com



File 123016

June 23, 2023

Rick Wallace 625007 SR 15 Melancthon, Ontario L0N 1S6 rwallace65@sympatico.ca

Re: Strada Aggregates, Shelburne Quarry Domestic Well Monitoring Program

Dear Mr. Wallace:

Tatham Engineering Limited (Tatham) was retained by Strada Aggregates to continue the on-going domestic water well monitoring program for the Shelburne Quarry. Whitewater Hydrogeology Ltd (Whitewater), which as of January 2023 has fully integrated with Tatham, previously carried out the domestic water well monitoring program.

On October 4th, 2022, Whitewater installed an automatic water level datalogger in your drilled well after you expressed interest in the monitoring program. A water level datalogger is an instrument that automatically and continuously records fluctuations in water level. Water level data logs are stored in the datalogger's memory and are downloaded for analysis.

The water level data is presented in the hydrograph appended to this letter. The water level is shown in black and has been calibrated to the manual measurement taken at the time the datalogger device was installed. A complete year cycle of groundwater monitoring is not available yet for your well; however, the water level data collected to date shows two different trends; 1) a seasonal response: the slow decline in water levels during the fall months; 2) daily trends: the instantaneous drawdown and recovery because of the daily water use and pump activation. These downward spikes in the data represent the times your well is in operation and supplying water to your home and are completely normal. The data suggests that the well has sufficient supply for domestic use.

On October 4th, 2022, a groundwater sample was taken from your water well and tested for various parameters. Results have been compared against Ontario Drinking Water Quality Standards (ODWQS) for both health and aesthetic maximums. The results of this test are appended.

The water sample indicated compliance with the ODWQS for the parameters tested with the exception of hardness with a measured concentration of 333 mg/L compared to a ODWQS Operational Guideline of 80 to 100 mg/L.





The operational guideline for hardness is set between 80 and 100 mg/L (ODWQS, 2006). Hardness is caused by dissolved calcium and magnesium and is expressed as the equivalent quantity of calcium carbonate. When heated, hard water tends to form scale deposits and can form excessive scum with regular soaps. However, there are certain detergents, which are largely unaffected by hardness. Conversely, water that is too soft may result in accelerated corrosion of water pipes. Hardness levels between 80 and 100 mg/L as calcium carbonate (CaCO3) is considered an acceptable balance between corrosion and incrustation. Water supplies with hardness greater then 200 mg/L are considered poor but tolerable. Hardness more than 500 mg/L in drinking water is unacceptable for most domestic purposes.

Please keep this information on file for your reference. Tatham will be providing a similar letter report to update you annually (or more frequently, if requested).

If you have any questions, feel free to call or email at any time.

Yours truly,

Tatham Engineering Limited

Alicia Kimberley, MSc., P.Geo.

Group Lead - Hydrogeology

JRM/AK/DT:ha

I:\2023 Projects\123016 - Strada - Shelburne\04 - ARA Submission\Documents\Reports\Domestic Well Reports\Strada Letters\DW5\Wallace (DW5) Letter 2023.docx

Daniel Twigger, B.Sc.Eng., P.Eng.

Manager - Water Resources Engineering

